

CableHome CAP MIB Specification

Superseded

CH-SP-MIB-CAP-I08-050211

Issued

Notice

This CableHome® specification is a cooperative effort undertaken at the direction of Cable Television Laboratories, Inc. (CableLabs®) for the benefit of the cable industry. Neither CableLabs, nor any other entity participating in the creation of this document, is responsible for any liability of any nature whatsoever resulting from or arising out of use or reliance upon this document by any party. This document is furnished on an AS-IS basis and neither CableLabs, nor other participating entity, provides any representation or warranty, express or implied, regarding its accuracy, completeness, or fitness for a particular purpose.

© Copyright 2001 - 2005 Cable Television Laboratories, Inc.

All rights reserved.

Document Status Sheet

Document Control Number:	CH-SP-MIB-CAP-I08-050211		
Document Title:	CableHome CAP MIB Specification		
Revision History:	I08 – February 11, 2005 I07 – December 16, 2004 I06 – August 6, 2004 I05 – January 29, 2004 I04 – August 1, 2003 I03 – April 11, 2003 I02 – September 20, 2002 I01 – April 5, 2002 D03 – March 21, 2002 D02 – January 31, 2002 D01 – January 8, 2002		
Date:	February 11, 2005		
Status:	Work in Progress	Draft	Issued
Distribution Restrictions:	Author Only	CL/Member	Public
		CL/ CableHome/Ve ndor	

Key to Document Status Codes:

- Work in Progress** An incomplete document, designed to guide discussion and generate feedback, which may include several alternative requirements for consideration.
- Draft** A document in specification format considered largely complete, but lacking review by Members and vendors. Drafts are susceptible to substantial change during the review process.
- Issued** A stable document, which has undergone rigorous member and vendor review and is suitable for product design and development, cross-vendor interoperability, and for certification testing.
- Closed** A static document, reviewed, tested, validated, and closed to further engineering change requests to the specification through CableLabs.

Trademarks:

DOCSIS®, eDOCSIS™, PacketCable™, CableHome®, CableOffice™, CableCARD™, OpenCable™ and CableLabs® are trademarks of Cable Television Laboratories, Inc.

CONTENTS

1 SCOPE1

2 REFERENCES1

2.1 Normative References 1

2.2 Reference Acquisition 1

3 ACRONYMS1

4 REQUIREMENTS2

5 ACKNOWLEDGEMENTS15

APPENDIX I REVISION HISTORY16

This page left blank intentionally.

1 SCOPE

This specification describes CableHome Addressing Portal (CH-AP) MIB (Management Information Base) definition.

2 REFERENCES

2.1 Normative References

In order to claim compliance with this specification, it is necessary to conform to the following standards and other works as indicated, in addition to the other requirements of this specification. Notwithstanding, intellectual property rights may be required to use or implement such normative references.

- [1] CableHome 1.0 Specification, CH-SP-CH1.0-I05-030801, August 1, 2003.
- [2] CableHome 1.1 Specification, CH-SP-CH1.1-I07-050211, February 11, 2005
- [3] CableLabs® Definition MIB Specification, CL-SP-MIB-CLABDEF-I04-040804, August 4, 2004.

2.2 Reference Acquisition

CableLabs Specifications:

- Cable Television Laboratories, Inc., <http://www.cablelabs.com/projects/cablehome/specifications/>

3 ACRONYMS

This specification uses the following acronyms:

CAP	CableHome Addressing Portal
CDC	CableHome DHCP Client (component of CDP)
CDP	CableHome DHCP Portal
CDS	CableHome DHCP Server (component of CDP)
CMP	CableHome Management Portal
CTP	CableHome Test Portal
DHCP	Dynamic Host Configuration Protocol
NAPT	Network Address and Port Translation
NAT	Network Address Translation
PS	Portal Services

4 REQUIREMENTS

The CableHome CAP MIB MUST be implemented as defined below.

```

CABH-CAP-MIB DEFINITIONS ::= BEGIN
IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Unsigned32,
    Integer32           FROM SNMPv2-SMI
    TimeStamp,
    TruthValue,
    RowStatus,
    DateAndTime,
    PhysAddress         FROM SNMPv2-TC
    OBJECT-GROUP,
    MODULE-COMPLIANCE  FROM SNMPv2-CONF
    InetAddressType,
    InetAddress,
    InetPortNumber     FROM INET-ADDRESS-MIB
    clabProjCableHome  FROM CLAB-DEF-MIB
    SntpAdminString    FROM SNMP-FRAMEWORK-MIB;

cabhCapMib MODULE-IDENTITY
    LAST-UPDATED      "200502110000Z" --February 11, 2005
    ORGANIZATION      "CableLabs Broadband Access Department"
    CONTACT-INFO
        "Kevin Luehrs
        Postal: Cable Television Laboratories, Inc.
        858 Coal Creek Circle
        Louisville, Colorado 80027
        U.S.A.
        Phone:  +1 303-661-9100
        Fax:    +1 303-661-9199
        E-mail: k.luehrs@cablelabs.com; mibs@cablelabs.com"
    DESCRIPTION
        "This MIB module supplies the basic management objects
        for the CableHome Addressing Portal (CAP) portion of
        the PS."
    ::= { clabProjCableHome 3 }

cabhCapObjects      OBJECT IDENTIFIER ::= { cabhCapMib 1 }
cabhCapBase         OBJECT IDENTIFIER ::= { cabhCapObjects 1 }
cabhCapMap          OBJECT IDENTIFIER ::= { cabhCapObjects 2 }

-----
--
--   General CAP Parameters
--
-----

cabhCapTcpTimeWait OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "seconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This object is the maximum inactivity time to wait before

```

assuming TCP session is terminated. It has no relation to the TCP session TIME_WAIT state referred to in [RFC793]."

REFERENCE
 "CableHome 1.1 Specification, Packet Handling & Address Translation section."

DEFVAL { 300 }
 ::= { cabhCapBase 1 }

cabhCapUdpTimeWait OBJECT-TYPE
 SYNTAX Unsigned32
 UNITS "seconds"
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "The inactivity time to wait before destroying CAP mappings for UDP."
 REFERENCE
 "CableHome 1.1 Specification, Packet Handling & Address Translation section."
 DEFVAL { 300 } -- 5 minutes
 ::= { cabhCapBase 2 }

cabhCapIcmpTimeWait OBJECT-TYPE
 SYNTAX Unsigned32
 UNITS "seconds"
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "The inactivity time to wait before destroying CAP mappings for ICMP."
 REFERENCE
 "CableHome 1.1 Specification, Packet Handling & Address Translation section."
 DEFVAL { 300 } -- 5 minutes
 ::= { cabhCapBase 3 }

cabhCapPrimaryMode OBJECT-TYPE
 SYNTAX INTEGER {
 napt(1), -- NAT with Port Translation Mode
 nat(2), -- Traditional NAT Mode
 passthrough(3) -- Passthrough/Bridging Mode
 }
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "The Primary Packet-handling Mode of the Portal Services logical element (PS) of a CableHome compliant residential gateway device. This object configures operation of the PS packet handling functions.

 When the value of this object is napt(1), the PS is required to support the Network Address and Port Translation (NAPT) process in accordance with the NAPT requirements defined in IETF RFC 3022. When operating in NAPT Primary Packet Handling Mode, the PS supports the translation of multiple LAN-Trans IP addresses and their TCP/UDP ports into a single WAN-Data IP address and its TCP/UDP ports.

 When the value of this object is nat(2), the PS is required to support the Network Address Translation (NAT) process in accordance with the NAT requirements defined in IETF RFC 3022. When operating in NAT Primary Packet Handling Mode,

the PS supports the translation of multiple LAN-Trans IP addresses into the same number of unique WAN-Data IP addresses.

When the value of this object is passthrough(3), the PS is required to act as a transparent bridge in accordance with IEEE 802.1D. When operating in Passthrough Primary Packet Handling Mode, the PS does not translate network addresses, and bridges all traffic between its LAN and WAN interfaces.

The PS MUST delete dynamically-created row entries from the cabhCapMappingTable, i.e. those with cabhCapMappingMethod = dynamic(2), when the value of cabhCapPrimaryMode changes. The PS MUST NOT delete statically-created row entries from the cabhCapMappingTable where cabhCapMappingMethod = static(1), when the value of cabhCapPrimaryMode changes."

REFERENCE

"CableHome 1.1 Specification, Packet Handling & Address Translation section."

DEFVAL { napt }

::= { cabhCapBase 4 }

cabhCapSetToFactory OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Reading this object always returns false(2). When the cabhCapSetToFactory object is set to true(1), the PS must take the following actions:

1. Clear all entries in the cabhCapMappingTable and cabhCapPassthroughTable.
2. Reset the following objects to their factory default values:
 - cabhCapTcpTimeWait,
 - cabhCapUdpTimeWait,
 - cabhCapIcmpTimeWait,
 - cabhCapPrimaryMode"

REFERENCE

"CableHome 1.1 Specification, Packet Handling & Address Translation section."

::= { cabhCapBase 5 }

cabhCapLastSetToFactory OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime when cabhCapSetToFactory was last set to true. Zero if never reset."

::= { cabhCapBase 6 }

cabhCapUpnpPortForwardingEnable OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This MIB is effective only when the PS is performing NAPT. If this MIB object is set to false(2), the PS MUST disable the UPnP WANIpConnection Service in the CableHome PS. If this MIB object is set to true(1), the PS MUST enable the

WANIpConnection service in the PS. When the primary packet handling mode of the PS is C-NAT (2) or Passthrough(3), setting this MIB to true(1) MUST return InconsistentValue error."

REFERENCE

"CableHome 1.1 Specification, Packet Handling & Address Translation section."

DEFVAL { 1 }

::= { cabhCapBase 7 }

cabhCapUpnpTimeWait OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The inactivity time to wait before destroying CAP mappings created by UPnP control points. The value of 0 indicates inactivity time wait of infinity, i.e. a UPnP entry doesn't get destroyed based on inactivity period."

REFERENCE

"CableHome 1.1 Specification, Packet Handling & Address Translation section."

DEFVAL { 0 } -- 0 seconds, inactivity time wait of infinity.

::= { cabhCapBase 8 }

```

=====
--
-- cabhCapMappingTable (CAP Mapping Table)
--
-- The cabhCapMappingTable contains information pertaining to all
-- NAPT and NAT mappings in a CableHome(TM) compliant residential
-- gateway device.
--
=====

```

cabhCapMappingTable OBJECT-TYPE

SYNTAX SEQUENCE OF CabhCapMappingEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains IP address mappings between private network addresses, or network addresses and port numbers/ICMP Identifiers, assigned to devices on the subscriber's home LAN, and network addresses, or network addresses and port numbers/ICMP Identifiers on the WAN, presumed to be on a separate subnetwork than the private IP addresses. The CAP Mapping Table is used by the CableHome Address Portal (CAP) function of the PS to make packet forwarding decisions."

REFERENCE

"CableHome 1.1 Specification, Packet Handling & Address Translation section."

::= { cabhCapMap 1 }

cabhCapMappingEntry OBJECT-TYPE

SYNTAX CabhCapMappingEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

```

        "List of the private IP (LAN) address - to - cable
        operator assigned IP (WAN) address mappings stored
        in the PS and used by the PS to make packet
        forwarding decisions."
INDEX { cabhCapMappingIndex }
 ::= { cabhCapMappingTable 1 }

CabhCapMappingEntry ::= SEQUENCE {
    cabhCapMappingIndex          INTEGER,
    cabhCapMappingWanAddrType    InetAddressType,
    cabhCapMappingWanAddr        InetAddress,
    cabhCapMappingWanPort        InetPortNumber,
    cabhCapMappingLanAddrType    InetAddressType,
    cabhCapMappingLanAddr        InetAddress,
    cabhCapMappingLanPort        InetPortNumber,
    cabhCapMappingMethod         INTEGER,
    cabhCapMappingProtocol       INTEGER,
    cabhCapMappingRowStatus      RowStatus,
    cabhCapMappingNumPorts       Unsigned32,
    cabhCapMappingRowDescr       SnmpAdminString,
    cabhCapMappingCreateTime     DateAndTime,
    cabhCapMappingLastUpdateTime DateAndTime,
    cabhCapMappingDuration       INTEGER32,
    cabhCapMappingRemoteHostAddrType InetAddressType,
    cabhCapMappingRemoteHostAddr InetAddress,
    cabhCapMappingEnable         TruthValue
}

cabhCapMappingIndex OBJECT-TYPE
    SYNTAX      INTEGER      (1..65535)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The Index into the CAP Mapping Table."
    ::= { cabhCapMappingEntry 1 }

cabhCapMappingWanAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The IP address type assigned on the WAN side."
    DEFVAL { ipv4 }
    ::= { cabhCapMappingEntry 2 }

cabhCapMappingWanAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The IP address assigned by the cable operator's address
        (DHCP) server, and comprising the WAN-side IP address
        of the CAP Mapping tuple. This object is populated
        either dynamically by LAN-to-WAN outbound traffic or
        statically by the cable operator."
    ::= { cabhCapMappingEntry 3 }

cabhCapMappingWanPort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The TCP/UDP port number or ICMP Identifier

```

```

        on the WAN side. A port number/Identifier of
        0 indicates either a NAT or a DMZ mapping.
        A non-zero port number/Identifier indicates
        a NAPT mapping. If the value of
        cabhCapMappingNumPorts MIB object is non-zero
        this MIB represents a starting TCP/UDP port
        number on the WAN side for which a mapping
        entry is created."
    DEFVAL { 0 }
    ::= { cabhCapMappingEntry 4 }

cabhCapMappingLanAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The IP address type assigned on the LAN side."
    DEFVAL { ipv4 }
    ::= { cabhCapMappingEntry 5 }

cabhCapMappingLanAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The IP address of the LAN-Trans IP Device. This object is
        populated either dynamically as a result of LAN-to-WAN
        outbound traffic or statically by the cable operator."
    ::= { cabhCapMappingEntry 6 }

cabhCapMappingLanPort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The TCP/UDP port number or ICMP Identifier
        on the LAN side. A port number/Identifier
        of 0 indicates either a DMZ mapping or a NAT
        mapping. A non-zero port number/Identifier
        indicates a NAPT mapping. If the value of
        cabhCapMappingNumPorts MIB object is non-zero
        then this MIB represents a starting TCP/UDP port
        number on the LAN side for which a mapping
        entry is created."
    DEFVAL { 0 }
    ::= { cabhCapMappingEntry 7 }

cabhCapMappingMethod OBJECT-TYPE
    SYNTAX      INTEGER {
                static(1),
                dynamic(2),
                upnp(3)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates how this mapping was created. Static means
        that it was provisioned, and dynamic means that it
        was handled by the PS itself. upnp (3) means that the
        CAP mapping entry was created by some UPnP compliant
        application."
    ::= { cabhCapMappingEntry 8 }

```

```

cabhCapMappingProtocol OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),    -- any other protocol; e.g. IGMP
        icmp(2),
        udp(3),
        tcp(4),
        all(255)     -- covers all the protocols
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The protocol for this mapping entry. The value
        of other(1) represents a protocol other
        than ICMP, TCP, and UDP. Thus, when the value
        other(1) is specified for the cabhCapMappingProtocol
        value of a CAP Mapping Table entry,
        TCP, UDP or ICMP packets MUST NOT be forwarded even
        if the WAN and LAN IP address and port tuple
        of the packet matches with mapping entry.
        The value of all(255) represents all protocol types. Thus,
        when the cabhCapMappingProtocol value
        all(255) is specified for an entry in the CAP Mapping
        Table, traffic of all protocol types MUST be forwarded
        accordingly if the WAN and LAN IP address and port tuple
        in the packet matches the mapping entry."
    ::= { cabhCapMappingEntry 9 }

```

```

cabhCapMappingRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The RowStatus interlock for the creation and deletion
        of a cabhCapMappingTable entry. Changing the value of
        the IP address or port number columns of the CAP
        Mapping Table may have an effect on active traffic,
        so the PS will prevent modification of this table's
        columns and return an inconsistentValue error when
        cabhCapMappingRowStatus object is active(1).

        The PS must not allow RowStatus to be set to
        notInService(2) by a manager.

        A newly created row cannot be set to active(1) until
        the corresponding instances of cabhCapMappingWanAddr,
        cabhCapMappingLanAddr, and cabhCapMappingProtocol have
        been set.

        If the manager attempts to populate a row entry in
        the table with a non-unique value for the combination
        of cabhCapMappingWanAddr and range of WAN port(s)
        (identified by cabhCapMappingWanPort to
        cabhCapMappingWanPort + cabhCapMappingNumPorts -1),
        or a non-unique value for the combination of
        cabhCapMappingLanAddr and range of LAN port(s)
        (identified by cabhCapMappingLanPort to
        cabhCapMappingLanPort + cabhCapMappingNumPorts - 1),
        the PS MUST prevent the creation of this row and return
        an inconsistentValue error. This prevents creation of
        entries with overlapping port ranges in the CAP table.

        If the manager attempts to populate a row entry with
        a zero value for cabhCapMappingWanPort and a non-zero

```

value for cabhCapMappingLanPort or a row entry with a zero value for cabhCapMappingLanPort and a non-zero value for cabhCapMappingWanPort, the PS MUST prevent the creation of this row and return an inconsistentValue error. This prevents creation of invalid NAT or NAPT entries.

If the manager attempts to populate a row entry with non-zero values for both cabhCapMappingWanPort and cabhCapMappingLanPort, but a zero value for cabhCapMappingNumPorts, the PS MUST prevent the creation of this row and return an inconsistentValue error. This prevents creation of NAPT entries.

When Primary Packet-handling Mode is NAPT (cabhCapPrimaryMode is napt(1)), provisioned rows can be set to active(1) regardless of whether the value to which cabhCapMappingWanPort, cabhCapMappingLanPort, and cabhCapMappingNumPorts have been set is zero or nonzero.

When Primary Packet-handling Mode is NAT (cabhCapPrimaryMode is nat(2)), a newly created row can not be set to active(1) if a non-zero value have been set for cabhCapMappingWanPort, cabhCapMappingLanPort and cabhCapMappingNumPorts.

In NAPT Primary Packet-handling mode, a row entry with zero values for cabhCapMappingWanPort, cabhCapMappingLanPort, and cabhCapMappingNumPorts objects represents a DMZ entry."

```
::={ cabhCapMappingEntry 10 }
```

cabhCapMappingNumPorts OBJECT-TYPE

SYNTAX Unsigned32(1..65535)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object represents number of ports available for port translation on both LAN and WAN side.

When both cabhCapMappingWanPort and cabhCapMappingLanPort are set to zero, the PS MUST ignore this MIB object, and such a row entry represents either a DMZ entry (when primary packet handling mode is NAPT) or a NAT entry (when primary packet handling mode is NAT).

When a row entry is created with non-zero values for cabhCapMappingWanPort, cabhCapMappingLanPort, and cabhCapMappingNumPorts the PS MUST translate range of ports on the WAN side (identified by cabhCapMappingWanPort to cabhCapMappingWanPort + cabhCapMappingNumPorts-1) to range of ports on the LAN side (identified by cabhCapMappingLanPort to cabhCapMappingLanPort + cabhCapMappingNumPorts-1).

The PS MUST ignore this MIB for a CAP mapping entry with the value of cabhCapMappingProtocol equal to icmp(2)."

```
DEFVAL { 1 }
```

```
::= { cabhCapMappingEntry 11 }
```

```

cabhCapMappingRowDescr OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(0..32))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "A string value that can be used to describe
         the purpose or attributes of the CAP Mapping
         entry."
    DEFVAL { "" }
    ::= { cabhCapMappingEntry 12 }

cabhCapMappingCreateTime OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "For dynamic(2) and upnp(3) CAP mapping entries the PS MUST
         set this MIB with date and time when the entry is created.
         The PS MUST set the value of this MIB to zero valued
         11-byte string for static CAP mapping entries. This MIB
         object MUST NOT persist across the PS reboot."
    ::= { cabhCapMappingEntry 13 }

cabhCapMappingLastUpdateTime OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The PS MUST set the value of this MIB
         to zero valued 11 byte string for static
         CAP mapping entries. For dynamic(2) CAP
         Mapping entries, the PS MUST set the value
         of this MIB to the value of cabhCapMappingCreateTime
         For upnp(3) CAP mapping entries the PS MUST
         set this MIB with date and time when the entry
         is last updated. When the upnp(3)entry is first
         created the PS MUST set this MIB with the value
         of cabhCapMappingCreateTime MIB. This MIB object
         MUST NOT persist across the PS reboot."
    ::= { cabhCapMappingEntry 14 }

cabhCapMappingDuration OBJECT-TYPE
    SYNTAX      Integer32 (-1|0..2147483647)
    UNITS       "seconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "When a value greater than zero
         is assigned to this object, the PS MUST
         remove the CAP entry after the time
         duration, represented by
         this object, elapses starting from
         cabhCapMappingLastUpdateTime.

         When a value of 0 is assigned to this object,
         the PS MUST retain the CAP mapping entry
         until reboot or reset. The PS MUST retain
         a CAP mapping entry with cabhCapMappingDuration
         MIB set to 0 and cabhCapMappingMethod set
         to static(1) across the reboots. The PS MUST
         NOT retain a CAP mapping entry with
         cabhCapMappingDuration MIB set to 0 and

```

cabhCapMappingMethod set to upnp(3) across the reboots.

When a value of -1 is assigned for this MIB the PS MUST ignore this MIB and MUST remove the CAP mapping entries based on TCP, UDP and ICMP inactivity time-wait depending upon their protocol type.

When the cabhCapMappingMethod object is static(1), the default value for this object is 0.

When the cabhCapMappingMethod object is dynamic(2), the PS MUST set the value of this object to -1.

When the cabhCapMappingMethod object is upnp(3), the default value for this object is -1."

```
::= { cabhCapMappingEntry 15 }
```

```
cabhCapMappingRemoteHostAddrType OBJECT-TYPE
```

```
SYNTAX      InetAddressType
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "The IP address type for a remote host on the WAN side."
```

```
DEFVAL { ipv4 }
```

```
::= { cabhCapMappingEntry 16 }
```

```
cabhCapMappingRemoteHostAddr OBJECT-TYPE
```

```
SYNTAX      InetAddress
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "The IP address of the remote host for a CAP mapping entry. The packet traversing through the PS is either originated from or is destined to this remote host. The value of all zeros for this MIB object indicates any IP address for a remote host."
```

```
DEFVAL { '00000000'h }
```

```
::= { cabhCapMappingEntry 17 }
```

```
cabhCapMappingEnable OBJECT-TYPE
```

```
SYNTAX      TruthValue
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "This MIB allows the PS to enable or disable a particular CAP mapping entry. When this MIB is set to true(1) for a CAP mapping entry, the PS MUST correctly route the traffic that matches this entry. When this MIB is set to false(2) for a CAP mapping entry, the PS MUST NOT route the traffic that matches this entry."
```

```
DEFVAL { true }
```

```
::= { cabhCapMappingEntry 18 }
```

```
-----
```

```

--
--   cabhCapPassthroughTable (CAP Passthrough Table)
--
--   The cabhCapPassthroughTable contains the hardware addresses
--   for all LAN IP Devices for which the PS will bridge traffic at
--   OSI Layer 2 when the PS's cabhCapPrimaryMode is set to forward
--   traffic at OSI Layer 3 (NAPT/NAT) for all other hardware
--   addresses.
--
-----

cabhCapPassthroughTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF CabhCapPassthroughEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains hardware addresses of LAN IP Devices
        for which the PS will bridge traffic at OSI Layer 2."
    REFERENCE
        "CableHome 1.1 Specification, Packet Handling & Address
        Translation section."
    ::= { cabhCapMap 2 }

cabhCapPassthroughEntry OBJECT-TYPE
    SYNTAX      CabhCapPassthroughEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "List of hardware addresses of LAN IP Devices for which
        the PS will bridge traffic at OSI Layer 2."
    INDEX { cabhCapPassthroughIndex }
    ::= { cabhCapPassthroughTable 1 }

CabhCapPassthroughEntry ::= SEQUENCE {
    cabhCapPassthroughIndex      INTEGER,
    cabhCapPassthroughMacAddr    PhysAddress,
    cabhCapPassthroughRowStatus  RowStatus
}

cabhCapPassthroughIndex OBJECT-TYPE
    SYNTAX      INTEGER (1..65535)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The index into the CAP Passthrough Table."
    ::= { cabhCapPassthroughEntry 1 }

cabhCapPassthroughMacAddr OBJECT-TYPE
    SYNTAX      PhysAddress (SIZE(0..16))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Hardware address of the LAN IP Device for which the PS
        MUST bridge traffic at OSI Layer 2."
    ::= { cabhCapPassthroughEntry 2 }

cabhCapPassthroughRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The RowStatus interlock for the creation and
        deletion of a cabhCapPassthroughTable entry."

```

```

        Any writable object in each row can be modified
        at any time while the row is active(1)."
 ::= { cabhCapPassthroughEntry 3 }
--
-- notification group is for future extension.
--

cabhCapNotification OBJECT IDENTIFIER ::= {
    cabhCapMib 2 0 }
cabhCapConformance OBJECT IDENTIFIER ::= {
    cabhCapMib 3 }
cabhCapCompliances OBJECT IDENTIFIER ::= {
    cabhCapConformance 1 }
cabhCapGroups OBJECT IDENTIFIER ::= {
    cabhCapConformance 2 }

--
-- Notification Group
--

-- compliance statements

cabhCapBasicCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for devices that implement
        the CableHome Portal Services functionality."
    MODULE --cabhCapMib

-- unconditionally mandatory groups

MANDATORY-GROUPS {
    cabhCapGroup
}

OBJECT cabhCapMappingProtocol
    SYNTAX INTEGER { icmp(2) }
    WRITE-SYNTAX INTEGER { other(1), udp(3), tcp(4), all(255) }
    DESCRIPTION
        "icmp(2) applies only to dynamic entries."

 ::= { cabhCapCompliances 1 }

cabhCapGroup OBJECT-GROUP
    OBJECTS {
        cabhCapTcpTimeWait,
        cabhCapUdpTimeWait,
        cabhCapIcmpTimeWait,
        cabhCapPrimaryMode,
        cabhCapSetToFactory,
        cabhCapLastSetToFactory,
        cabhCapMappingWanAddrType,
        cabhCapMappingWanAddr,
        cabhCapMappingWanPort,
        cabhCapMappingLanAddrType,
        cabhCapMappingLanAddr,
        cabhCapMappingLanPort,
        cabhCapMappingMethod,
        cabhCapMappingProtocol,
        cabhCapMappingRowStatus,
        cabhCapPassthroughMacAddr,

```

```
cabhCapPassthroughRowStatus,
cabhCapMappingNumPorts,
cabhCapMappingRowDescr,
cabhCapMappingCreateTime,
cabhCapMappingLastUpdateTime,
cabhCapMappingDuration,
cabhCapUpnpPortForwardingEnable,
cabhCapUpnpTimeWait,
cabhCapMappingRemoteHostAddrType,
cabhCapMappingRemoteHostAddr,
cabhCapMappingEnable
}
STATUS          current
DESCRIPTION
    "Group of objects for CableHome CAP MIB."
 ::= { cabhCapGroups 1 }
```

END

5 ACKNOWLEDGEMENTS

The following contributors deserve genuine gratitude for their efforts in the development of the CAP MIB specification.

Roy Spitzer, Consultant to CableLabs
Mike Mannette, Consultant to CableLabs
Randy Dunton of Intel
Dmitrii Loukianov of Intel
Itay Sherman of Texas Instruments
Chris Zacker of Broadcom
Rick Vetter, Consultant to CableLabs
John Bevilacqua of YAS

Appendix I Revision History

The following Engineering Change Notices were incorporated into CH-SP-MIB-CAP-I02-020920:

ECN Number	ECN Date	Summary
CH1-N-02007	6/20/02	Modify the default values of the CAP Mapping Table timeout values for UDP, TCP, and ICMP protocols.
CH1-N-02011	6/20/02	Eight technical/editorial changes.
CH1-N-02017	8/15/02	Four technical/editorial changes.
CH1-N-02019	8/15/02	Four technical/editorial changes.

The following Engineering Change Notices were incorporated into CH-SP-MIB-CAP-I03-030411:

ECN Number	ECN Date	Summary
CH1-N-02054	1/23/03	Provide more descriptive text in the CAP MIB for various tables and for Row Status of various tables.
CH1-N-03014	3/13/03	Clarify description of the cabhCapSetToFactory mib object.

The following Engineering Change Notices were incorporated into CH-SP-MIB-CAP-I04-030801:

ECN Number	ECN Date	Summary
CH1-N-03026	6/5/03	Define a Cap2MappingTable for CableHome 1.1, to support the static port forwarding feature.
CH-MIB-N-03052	7/3/03	Update CAP MIB to incorporate changes needed to align the CableLabs version with the version submitted to the IETF.

The following Engineering Change Notices were incorporated into CH-SP-MIB-CAP-I05-040129:

ECN Number	ECN Date	Summary
CH-MIB-N-03062	10/02/03	Update description related with change to ICMP sequence number.
MIB-CAP-N-03.0084-3	11/26/03	Removal of textual convention, CAP mapping table clarifications, and passthrough table clarifications.
MIB-CAP-N-03.0095-4	12/4/03	Add value of "all" for the protocol MIB in the CAP table.

The following Engineering Change Notices were incorporated into CH-SP-MIB-CAP-I06-040806:

ECN Number	ECN Date	Summary
MIB-CAP-N-04.0130-2	5/13/04	Define new Primary Packet Handling Mode option for CAP MIB: Disabled Mode
MIB-CAP-N-04.0136-3	5/20/04	CAP MIB changes to enable ports ranges and addition of other useful MIBs

The following Engineering Change Notices were incorporated into CH-SP-MIB-CAP-I07-041216

ECN Number	ECN Date	Summary
MIB-CAP-N-04.0191-2	11/11/04	CAP MIB changes to support corrections to CAP Mapping Table
MIB-CAP-N-04.0173-1	9/30/04	Remove 'disabled' option from cabhCapPrimaryMode object

The following Engineering Change Notices were incorporated into CH-SP-MIB-CAP-I08-050211

ECN Number	ECN Date	Summary
MIB-CAP-N-04.0199-3	1/13/05	Changes to support UPnP WANIpConnectionService