

This tech report has been closed and obsoleted by the
DOCSIS 2.0+IPv6 Cable Modem Specification

Data-Over-Cable Service Interface Specifications

DOCSIS 2.0 + IPv6 Cable Modem Technical Report

CM-TR-DOCSIS2.0-IPv6-V01-080307

RELEASED

Notice

This DOCSIS® technical report is the result of a cooperative effort undertaken at the direction of Cable Television Laboratories, Inc. for the benefit of the cable industry and its customers. This document may contain references to other documents not owned or controlled by CableLabs. Use and understanding of this document may require access to such other documents. Designing, manufacturing, distributing, using, selling, or servicing products, or providing services, based on this document may require intellectual property licenses from third parties for technology referenced in this document.

Neither CableLabs nor any member company is responsible to any party for any liability of any nature whatsoever resulting from or arising out of use or reliance upon this document, or any document referenced herein. This document is furnished on an "AS IS" basis and neither CableLabs nor its members provides any representation or warranty, express or implied, regarding the accuracy, completeness, noninfringement, or fitness for a particular purpose of this document, or any document referenced herein.

© Copyright 2008 Cable Television Laboratories, Inc.
All rights reserved.

Document Status Sheet

Document Control Number:	CM-TR-DOCSIS2.0-IPv6-V01-080307			
Document Title:	DOCSIS 2.0 + IPv6 Cable Modem Technical Report			
Revision History:	V01 – Released 3/07/08			
Date:	March 07, 2008			
Status:	Work in Progress	Draft	Released	Closed
Distribution Restrictions:	Author Only	CL/Member	CL/Member/Vendor	Public

Trademarks

CableLabs[®], DOCSIS[®], EuroDOCSIS[™], eDOCSIS[™], M-CMTS[™], PacketCable[™], EuroPacketCable[™], PCMM[™], CableHome[®], CableOffice[™], OpenCable[™], OCAP[™], CableCARD[™], M-Card[™], DCAS[™], and tru2way[™] are trademarks of Cable Television Laboratories, Inc.

Contents

1	INTRODUCTION	1
1.1	DOCSIS OVERVIEW	1
1.2	CONVENTIONS FOR THIS TECHNICAL REPORT	1
2	REFERENCES	2
2.1	NORMATIVE REFERENCES	2
2.2	INFORMATIVE REFERENCES	2
2.3	REFERENCE ACQUISITION	3
3	TERMS AND DEFINITIONS	4
4	ABBREVIATIONS AND ACRONYMS	5
5	CM INITIALIZATION	6
5.1	DOCSIS INITIALIZATION	6
5.1.1	<i>EAE</i>	6
5.1.2	<i>MDD Processing</i>	6
5.2	IP INITIALIZATION	6
5.2.1	<i>Establishing IP Connectivity</i>	6
5.2.2	<i>Establish IPv4 Network Connectivity</i>	7
5.2.3	<i>Establish IPv6 Network Connectivity</i>	7
5.2.4	<i>Establish Time of Day</i>	7
5.2.5	<i>Transfer Operational Parameters</i>	7
5.3	MODEM CAPABILITIES AND VENDOR CLASS REPORTING	7
5.4	CM REGISTRATION	8
5.5	TLV ENCODINGS	8
6	IPv6 TRAFFIC	9
6.1	MULTICAST HANDLING	9
6.1.1	<i>GMAC Explicit DSID Forwarding</i>	9
6.1.2	<i>IPv6 Multicast for MDF-incapable CMs</i>	10
6.2	FILTERING IPv6 TRAFFIC	10
7	MANAGEMENT	11
7.1	SNMP (SIMPLE NETWORK MANAGEMENT PROTOCOL)	11
7.2	MIB MODULE UPDATES	11
7.2.1	<i>IP-MIB [RFC 4293]</i>	11
7.2.2	<i>DOCS-CABLE-DEVICE-MIB [RFC 4639]</i>	11
7.2.3	<i>DOCS-IF-MIB [ID DOCS IF]</i>	11
7.2.4	<i>UDP-MIB [RFC 4113]</i>	12
7.2.5	<i>IGMP-STD-MIB [RFC 2933]</i>	12
7.2.6	<i>DOCS-QOS-MIB [OSSIv2.0] and DOCS-QOS3-MIB [OSSIv3.0]</i>	12
7.2.7	<i>DOCS-BPI2-MIB [ID BPI+]</i>	13
7.3	DOCSIS EVENTS	13
7.4	SNMP ACCESS REQUIREMENTS	14
8	CABLE MODEM SOFTWARE DOWNLOAD	16
APPENDIX I DHCPV6 OPTIONS		17
APPENDIX II ACKNOWLEDGEMENTS		18

List of Tables

TABLE 1 - DHCPV6 OPTIONS.....17

This tech report has been closed and obsoleted by the
DOCSIS 2.0+IPv6 Cable Modem Specification

1 INTRODUCTION

1.1 DOCSIS Overview

This Technical Report provides a set of guidelines for DOCSIS 2.0 Cable Modems to implement support for IPv6 Provisioning and Management as well as support for connected IPv6 eSAFEs and external CPE devices. The term 2.0+IPv6 Cable Modem is used to represent such Cable Modems. The use of IPv6 allows MSOs to conserve IPv4 addresses. This Technical Report provides guidelines for Cable Modems only.

1.2 Conventions for this Technical Report

In this technical report, the convention is that the CM is required to comply with the [RFIV2.0] specification for all behaviors not specified in this technical report.

As in [MULPIV3.0], the term "CPE" includes both externally connected CPE devices and eSAFEs. The term "CMCI port" describes physical interfaces to which externally connected CPE devices can attach. The term "Logical CPE Interface" refers to an interface between the CM and an eSAFE. The term "CPE interface" refers to an interface that is either a CMCI port or a Logical CPE Interface.

2 REFERENCES

2.1 Normative References

There are no normative references in this technical report.

2.2 Informative References

This technical report uses the following informative references.

- [DHCP-REG] CableLabs DHCP Options Registry Specification, CL-SP-CANN-DHCP-Reg-I02-080306, March 6, 2008, Cable Television Laboratories, Inc.
- [MULPIv3.0] DOCSIS Media Access Control and Upper Layer Protocols Interface Specification, CM-SP-MULPIv3.0-I07-080215, February 15, 2008, Cable Television Laboratories, Inc.
- [OSSIv2.0] DOCSIS Operations Support System Interface Specification, CM-SP-OSSIv2.0-I10-070803, August 3, 2007, Cable Television Laboratories, Inc.
- [OSSIv3.0] DOCSIS Operations Support System Interface Specification, CM-SP-OSSIv3.0-I06-080215, February 15, 2008, Cable Television Laboratories, Inc.
- [DOCSIS SECv3.0] Data-Over-Cable Service Interface Specifications, Security Specification, CM-SP-SECv3.0-I07-080215, February 16, 2008, Cable Television Laboratories, Inc.
- [ID DOCS IF] IETF Internet Draft, David Raftus, Radio Frequency (RF) Interface Management Information Base for DOCSIS 2.0 compliant RF interfaces, December 2002. Refer to <http://www.ipcdn.org/drafts/draft-ietf-ipcdn-docs-rfmibv2-05.txt>
- [ID BPI+] IETF Internet Draft, Stuart M. Green, Management Information Base for DOCSIS Cable Modems and Cable Modem Termination Systems for Baseline Privacy Plus, May 2001. Refer to <http://www.ipcdn.org/drafts/draft-ietf-ipcdn-bpiplus-mib-05.txt>
- [RFC 2013] IETF RFC 2013, RFC SNMPv2 Management Information Base for the User Datagram Protocol using SMIPv2, November 1996.
- [RFC 2132] IETF RFC 2132, DHCP Options and BOOTP Vendor Extensions, March 1997.
- [RFC 2462] IETF RFC 2462, IPv6 Stateless Address Autoconfiguration, December 1998.
- [RFC 2710] IETF RFC 2710, Multicast Listener Discovery (MLD) for IPv6, October 1999.
- [RFC 2933] IETF RFC 2933, Internet Group Management Protocol MIB, October 2000.
- [RFC 3315] IETF RFC 3315, Dynamic Host Configuration Protocol for IPv6 (DHCPv6), July 2003.
- [RFC 3419] IETF RFC 3419, Textual Conventions for Transport Addresses, December 2002.
- [RFC 3513] IETF RFC 3513, Internet Protocol Version 6 (IPv6) Addressing Architecture, April 2003.

- [RFC 4113] IETF RFC 4113, Management Information Base for the User Datagram Protocol (UDP), June 2005.
- [RFC 4291] IETF RFC 4291, IP Version 6 Addressing Architecture, February 2006.
- [RFC 4293] IETF RFC 4293, Management Information Base for the Internet Protocol (IP), April 2006.
- [RFC 4323] IETF RFC 4323, Data Over Cable System Interface Specification Quality of Service Management Information Base (DOCSIS-QoS MIB), January 2006.
- [RFC 4361] IETF RFC 4361, Node-specific Client Identifiers for Dynamic Host Configuration Protocol Version Four (DHCPv4), February 2006.
- [RFC 4605] IETF RFC 4605, Internet Group Management Protocol (IGMP) / Multicast Listener Discovery (MLD)-Based Multicast Forwarding (IGMP/MLD Proxying), August 2006.
- [RFC 4639] IETF RFC 4639, Cable Device Management Information Base for Data-Over-Cable Service Interface Specification (DOCSIS) Compliant Cable Modems and Cable Modem Termination Systems, December 2006.
- [RFIV1.1] DOCSIS 1.1, Radio Frequency Interface Specification, CM-SP-RFIV1.1-C01-050907, September 7, 2005, Cable Television Laboratories, Inc.
- [RFIV2.0] DOCSIS 2.0, Radio Frequency Interface Specification, CM-SP-RFIV2.0-I13-080215, February 15, 2008, Cable Television Laboratories, Inc.

2.3 Reference Acquisition

- Cable Television Laboratories, Inc., 858 Coal Creek Circle, Louisville, CO 80027; Phone +1-303-661-9100; Fax +1-303-661-9199; <http://www.cablelabs.com>
- Internet Engineering Task Force (IETF) Secretariat, 4600 Center Oak Plaza, Sterling, VA 20166, Phone +1-571-434-3500, Fax +1-571-434-3535, <http://www.ietf.org>
- Internet Engineering Task Force (IETF), Internet: <http://www.ietf.org/>
Note: Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time.
The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.
Internet-Drafts may also be accessed at <http://tools.ietf.org/html/>

3 TERMS AND DEFINITIONS

This DOCSIS Technical Report uses the following terms and definitions:

DOCSIS 2.0+IPv6 CM A DOCSIS 2.0 Cable Modem that supports IPv6 Provisioning and Management and supports connected IPv6 eSAFEs and external CPE devices.

Any terms used, but not defined in this document, can be found in the [MULPIv3.0] specification.

4 ABBREVIATIONS AND ACRONYMS

Any abbreviations or acronyms used in this document can be found in the [MULPIv3.0] specification.

5 CM INITIALIZATION

5.1 DOCSIS Initialization

5.1.1 EAE

The DOCSIS 2.0+IPv6 CM is not required to support Early Authentication and Encryption (EAE) per the *Early Authentication and Encryption (EAE)* section of [DOCSIS SECv3.0]. Because these CMs are not expected to support EAE, the recommended CMTS EAE enforcement configuration should be to enforce EAE via Policy 1 (No EAE Enforcement), Policy 2 (Ranging-based EAE Enforcement), or Policy 3 (Capability-based Enforcement). If EAE is enabled at the CMTS and the CMTS is configured to enforce EAE via Policy 4 (Total EAE Enforcement), the DOCSIS 2.0+IPv6 CM will not be able to register.

5.1.2 MDD Processing

As with DOCSIS 3.0, the DOCSIS 2.0+IPv6 CM is required to look for the presence of the DOCSIS 3.0 MAC Domain Descriptor (MDD) message [MULPIv3.0] on the downstream channel it has acquired during downstream scanning and synchronization. Because the MDD message may be fragmented when a MAC domain is complex, the DOCSIS 2.0 CM needs to parse the fragments of the MDD message, looking for the IP Provisioning TLV (TLV 5) and optionally for the DSG DA-to-DSID Association Entry TLV (TLV 13).

The IP provisioning mode is communicated in the IP Provisioning Mode TLV (TLV 5.1) as defined in the *IP Initialization Parameters TLV* section of [MULPIv3.0]. The DOCSIS 2.0+IPv6 CM is only required to support single stack IPv4 or single stack IPv6 operation. It is optional for this CM to support Alternate Provisioning mode and/or Dual Stack Provisioning mode.

If the DOCSIS 2.0+IPv6 CM is capable of GMAC Explicit Multicast DSID Forwarding, the DOCSIS 2.0+IPv6 CM is also required to utilize the Pre-Registration DSID (TLV 5.2) communicated in the MDD message. Additionally, if the DOCSIS 2.0+IPv6 CM that supports GMAC Explicit Multicast DSID Forwarding is an eCM with an eSTB, the CM needs to utilize the DSG DA-to-DSID Association Entry TLV (TLV 13) as defined in the *DSG DA-to-DSID Association Entry* section of [MULPIv3.0] to learn the DSID(s) associated with DSG tunnel(s).

5.2 IP Initialization

5.2.1 Establishing IP Connectivity

The DOCSIS 2.0+IPv6 CM determines the IP provisioning mode by the absence of the MDD message or by the TLVs in the MDD message. If the DOCSIS 2.0+IPv6 CM does not receive an MDD from the CMTS, the DOCSIS 2.0+IPv6 CM performs IPv4 provisioning as defined in Annex D of [RFIv2.0]. The MDD IP Provisioning Mode TLV signals to the DOCSIS 2.0+IPv6 CM one the following four IP provisioning modes:

- IPv4 Only
- IPv6 Only
- Alternate Provisioning Mode (APM)
- Dual-stack Provisioning Mode (DPM)

If the MDD IP Provisioning Mode TLV signals IPv4 Only provisioning, the DOCSIS 2.0+IPv6 CM performs IPv4 provisioning as defined in [RFIv2.0]. If the MDD IP Provisioning Mode TLV signals IPv6 Only provisioning, the DOCSIS 2.0+IPv6 CM performs IPv6 Only provisioning as defined in the *Establishing IP Connectivity* section of [MULPIv3.0].

The DOCSIS 2.0+IPv6 CM may implement APM. If it does not, when the MDD IP Provisioning Mode TLV signals APM the DOCSIS 2.0+IPv6 CM defaults to IPv4 Only or IPv6 Only provisioning. Defaulting to IPv4 Only provisioning is recommended. The DOCSIS 2.0+IPv6 CM implementation of APM is as defined in the *Establishing IP Connectivity* and the *Alternate Provisioning Mode (APM) Operation* sections of [MULPIv3.0], with the exception that IPv4 provisioning is done per [RFIv2.0].

The DOCSIS 2.0+IPv6 CM may implement DPM. If it does not, when the MDD IP Provisioning Mode TLV signals DPM, the DOCSIS 2.0+IPv6 CM defaults to IPv4 Only provisioning, IPv6 Only provisioning, or APM. Defaulting to IPv4 Only provisioning is recommended. The DOCSIS 2.0+IPv6 CM implementation of DPM is as defined in the *Establishing IP Connectivity* and the *Dual-stack Provisioning Mode (DPM)* sections of [MULPIv3.0], with the exception that IPv4 provisioning is done per [RFIv2.0].

MULPIv3.0 specifies the use of the DHCPv6-style client identifier for DHCPv4 [RFC 4361], while RFIv2.0 assumes the DHCPv4 client will use a client identifier as specified in section 9.14 of [RFC 2132]. Therefore, any management application that correlates the DHCPv4 identifier and the DHCPv6 identifier for a CM will need to be aware of the different DHCPv4 client identifier formats and use a different correlation computation for a CM provisioned according to this technical report.

5.2.2 Establish IPv4 Network Connectivity

The DOCSIS 2.0+IPv6 CM establishes IPv4 connectivity using DHCPv4 as defined in Annex D of [RFIv2.0]. During DHCPv4 renew and rebind operations, the DOCSIS 2.0+IPv6 CM processes DHCPACK messages and behaves as defined in Annex D of [RFIv2.0].

5.2.3 Establish IPv6 Network Connectivity

The DOCSIS 2.0+IPv6 CM establishes IPv6 connectivity as defined in the *Establish IPv6 Network Connectivity* section and associated subsections of [MULPIv3.0]. During DHCPv6 renew and rebind operations, the DOCSIS 2.0+IPv6 CM processes DHCPv6 Reply messages and behaves as defined in the *DHCPv6 Renew Fields Used by the CM* section of [MULPIv3.0].

5.2.4 Establish Time of Day

The DOCSIS 2.0+IPv6 CM establishes date and time as defined in [RFIv2.0] when using either IPv6 or IPv4 as the network protocol.

5.2.5 Transfer Operational Parameters

The DOCSIS 2.0+IPv6 CM downloads a configuration file using TFTP as defined in [RFIv2.0] when using either IPv6 or IPv4 as the network protocol. For the download over IPv6, the DOCSIS 2.0+IPv6 CM has the option to select only the first TFTP server address listed in the DHCPv6 TFTP Server Addresses option.

5.3 Modem Capabilities and Vendor Class Reporting

The DOCSIS 2.0+IPv6 CM includes the modem capabilities in the DHCP messages (Modem Capabilities encodings) and Registration Request messages as defined in [RFIv2.0] with the exceptions described below.

A DOCSIS 2.0+IPv6 CM reports a DOCSIS Version (TLV 5.2) of “DOCSIS v2.0” in all interactions with provisioning servers and CMTS registration messages per [RFIv2.0]. The DOCSIS 2.0+IPv6 CM reports the following additional capabilities in the Modem Capabilities encodings of the DHCP and Registration Request messages per [MULPIv3.0]:

- Multicast DSID Support (TLV 5.32)
- Multicast DSID Forwarding (TLV5.33)

- Frame Control Type Forwarding (TLV 5.34)
- IPv6 Support (TLV 5.39) = 1

The DOCSIS 2.0+IPv6 CM optionally reports the Upstream Drop Classifier Support capability (TLV 5.38) in the Modem Capabilities encodings of the DHCP and Registration Request messages.

The values reported in these capabilities depend on the type of IPv6 support provided by the DOCSIS 2.0+IPv6 CM and are described in the *GMAC Explicit DSID Forwarding*, *IPv6 Multicast for MDF Incapable CMs*, and *Filtering IPv6 Traffic* sections of this document.

The capabilities are carried in DHCPv4 messages as defined in [RFIV2.0] and in DHCPv6 messages as defined in [MULPIV3.0].

A DOCSIS 2.0+IPv6 CM reports “docsis2.0:xxxxxxx” in the DHCPv4 Vendor Class Identifier option per [RFIV2.0].

A DOCSIS 2.0+IPv6 CM reports a DHCPv6 Vendor Class option containing 32-bit number 4491 (the Cable Television Laboratories, Inc. enterprise number) and the string "docsis2.0".

5.4 CM Registration

The DOCSIS 2.0+IPv6 CM registers with a CMTS as defined in [RFIV2.0].

5.5 TLV Encodings

The DOCSIS 2.0+IPv6 CM supports the TLV encodings defined in [RFIV2.0]. The DOCSIS 2.0+IPv6 CM additionally supports the TLV encodings defined in [MULPIV3.0] that are described in this document.

6 IPV6 TRAFFIC

6.1 Multicast handling

Devices on an IPv6 network communicate using several well-known multicast addresses per [RFC 4291].

Prior to registration, a DOCSIS 2.0+IPv6 CM is required to forward packets addressed to certain well-known multicast addresses to its IP stack. The well-known IPv6 Addresses include the IPv6 Link Local Scope All Nodes Address (33-33-00-00-00-01, FF02::1) and the Solicited Node Addresses. The DOCSIS 2.0+IPv6 CM calculates the Link Local Solicited Node Address (33-33-ff-xx-xx-xx, FF02:0:0:0:1:FFxx:xxxx) based on its MAC address per [RFC 3513]. The DOCSIS 2.0+IPv6 CM sends MLDv1 join messages for its solicited node multicast addresses for both the calculated link-local address and the MSO assigned global IPv6 address.

The DOCSIS 2.0+IPv6 CM is required to forward the multicast traffic necessary for IPv6 CPE provisioning. This traffic includes the well-known IPv6 multicast traffic addressed to the All-Nodes multicast address and to the Solicited-Node multicast addresses. This report allows for two methods of supporting this multicast forwarding.

6.1.1 GMAC Explicit DSID Forwarding

This report allows a DOCSIS 2.0+IPv6 CM to support GMAC Explicit DSID Forwarding as described in the *GMAC-Explicit Multicast DSID Forwarding Mode* section of [MULPIv3.0]. GMAC Explicit DSID Forwarding means that the DOCSIS 2.0+IPv6 CM supports DSID forwarding of multicast traffic per the *DSID based Filtering and Forwarding by a Cable Modem* section of [MULPIv3.0], but performs filtering of multicast traffic based on the Group MAC Address.

Prior to registration, a DOCSIS 2.0+IPv6 CM that is capable of GMAC Explicit DSID Forwarding filters multicast traffic not addressed to the IPv6 Link Local Scope All Nodes Address or the Solicited Node Addresses. This CM learns the pre-registration DSID from the MDD message and forwards pre-registration multicast traffic to its IP stack based on the pre-registration DSID as defined in the *DSID based Filtering and Forwarding by a Cable Modem* section of [MULPIv3.0].

The DOCSIS 2.0+IPv6 CM reports the following capabilities in the Registration Request message.

- Multicast DSID Support (TLV 5.32) = number of multicast DSIDs supported by CM
- Multicast DSID Forwarding (TLV5.33) = 1
- Frame Control Type Forwarding (TLV 5.34) = 0 or 1

The CMTS may disable Multicast DSID Forwarding on the CM by confirming a value of 0 in the Multicast DSID Forwarding capability in the Registration Response message per [MULPIv3.0]. If the CMTS disables Multicast DSID Forwarding, the CM continues to forward to its IP stack packets addressed to the IPv6 All Nodes address, the Solicited Node multicast address calculated from its link-local address, and the Solicited Node multicast address calculated from the MSO assigned global IPv6 address. The CM performs IGMPv2 snooping per [RFIV2.0] and cannot forward IPv6 multicast to the CPE interfaces.

If the CMTS confirms a value of 1 in the Multicast DSID Forwarding capability in the Registration Response message, the CM stops forwarding multicast traffic labeled with the Pre-Registration DSID upon the receipt of the REG-RSP message. The CM programs the DSIDs and Group MAC Addresses communicated in the Registration Response message. The CMTS includes multicast traffic addressed to the IPv6 Link Local Scope All Nodes Address and the CM's Solicited Node Addresses in the DSIDs and Group MAC Addresses communicated in the Registration Response message.

The GMAC Explicit CM is required to support the use of Multicast DSID Encodings (TLV 50.4) described in the *Multicast Encodings* section of [MULPIv3.0] as well as the Security Association Encodings (TLV 51) described in the *Security Association Encoding* section of [MULPIv3.0] in a Registration Response message.

The GMAC Explicit CM is required to support the use of the Dynamic Bonding Change mechanism per [MULPIv3.0] to maintain and learn new DSID values and Security Associations for IP Multicast. The GMAC Explicit CM performs a Dynamic Bonding Change (DBC) operation when it receives a DBC-REQ message containing only Multicast DSID Encodings (TLV 50.4) or Security Association Encodings (TLV 51). The DOCSIS 2.0+IPv6 CM rejects a DBC-REQ message with any encodings other than the Multicast DSID Encodings or Security Association Encodings.

The GMAC Explicit CM supports DSID indexed PHS.

6.1.2 IPv6 Multicast for MDF-incapable CMs

This report alternatively allows a DOCSIS 2.0+IPv6 CM that is unable to implement DSID forwarding to support CPE IPv6 provisioning through other means. The MDF-incapable CM supports only the multicast forwarding necessary for provisioning of an IPv6 CPE.

Prior to registration, the MDF-incapable CM forwards the well-known IPv6 multicast traffic packets to its IP stack based on the group MAC addresses. This CM requires no knowledge of the Pre-Registration DSID in order to forward this traffic.

The DOCSIS 2.0+IPv6 CM signals support for multicast forwarding capabilities other than MDF by reporting the following capabilities in the Registration Request message.

- Multicast DSID Support (TLV 5.32) = 0
- Multicast DSID Forwarding (TLV 5.33) = 0
- Frame Control Type Forwarding (TLV 5.34) = 0

After registration, the MDF-incapable CM continues to forward to its IP stack packets addressed to the IPv6 All Nodes address, the Solicited Node multicast address calculated from its link-local address, and the Solicited Node multicast address calculated from the MSO assigned global IPv6 address.

The MDF-incapable CM is responsible for forwarding Neighbor Discovery packets sent to CPEs Solicited Node multicast IPv6 addresses and to the All-Nodes multicast address onto CPE ports. This CM forwards these multicast packets always unless administratively prohibited via the configuration of filters.

The definition of the multicast forwarding mechanism for MDF-incapable CMs is vendor proprietary. The CM, for example, may forward onto CPE ports all traffic matching the multicast MAC address 33-33-FF-xx-xx-xx. As another example, the CM may learn CPE Solicited Node multicast addresses via snooping of the Neighbor Discovery or Duplicate Address Detection packets sent by CPE, and forward traffic matching these addresses only.

6.2 Filtering IPv6 Traffic

In order to provide IPv6 filtering support for devices forwarding IPv6 traffic to the CMCI ports, the DOCSIS 2.0+IPv6 CM may support IPv6 classification and upstream drop classification per [MULPIv3.0]. The DOCSIS 2.0+IPv6 CM reports a value of 1 for the Upstream Drop Classification Support capability (TLV 5.39) in the Registration Request message to indicate support for Upstream Drop Classification and for IPv6 classification.

For DOCSIS 2.0+IPv6 CMs that do not support Upstream Drop Classification, the MSO has the option of configuring the Subscriber Management MIB at the CMTS to perform this function.

7 MANAGEMENT

7.1 SNMP (Simple Network Management Protocol)

The DOCSIS 2.0+IPv6 CM is required to support SNMP over IPv6 as defined in the section *Requirements for IPv6* in [OSSIV3.0].

7.2 MIB Module Updates

In order to accommodate the introduction of IPv6 addresses, several of the DOCSIS 2.0 MIBs have been updated. The following sections detail the MIB implementations for the DOCSIS 2.0+IPv6 CM.

7.2.1 IP-MIB [RFC 4293]

The RFC 4293 MIB is required in a DOCSIS 2.0+IPv6 CM. This MIB replaces both RFC 2011 and RFC 2012. This MIB must be implemented per the guidelines in [OSSIV3.0].

7.2.2 DOCS-CABLE-DEVICE-MIB [RFC 4639]

A DOCSIS 2.0+IPv6 CM is required to support the requirements for [RFC 4639] defined in [OSSIV3.0].

7.2.3 DOCS-IF-MIB [ID DOCS IF]

A DOCSIS 2.0+IPv6 CM continues to support the IETF draft of the RFI MIB version 5. The object docsIfCmStatusValue is extended to align with the DOCSIS 3.0 CmRegState Textual Convention in DOCS-IF3-MIB.

```
docsIfCmStatusValue OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),
        notReady(2),
        notSynchronized(3),
        phySynchronized(4),
        usParametersAcquired(5),
        rangingInProgress(22),
        rangingComplete(6),
        eaeInProgress(14), -- Not Applicable
        dhcpv4InProgress(15),
        dhcpv6InProgress(16),
        dhcpv4Complete(7),
        dhcpv6Complete(17),
        todEstablished(8),
        securityEstablished(9),
        configFileDownloadComplete(10),
        registrationInProgress(18),
        registrationComplete(11),
        accessDenied(13),
        operational(12),
        bpiInit(19),
        forwardingDisabled(20),
        dsTopologyResolutionInProgress(21), -- Not Applicable
        rfMuteAll(23) -- Not Applicable
    }

    MAX-ACCESS  read-only
    STATUS      current
```

DESCRIPTION

"Current Cable Modem connectivity state, as specified in the RF Interface Specification. Interpretations for state values. This list has been modified for DOCSIS 2.0 CM supporting IPv6 to align it with the states identified in the CmRegState TC.

The state value accessDenied(13) indicates the CMTS has sent a Registration Aborted message to the CM. The same state is reported as accessDenied(7) by the CMTS object docsIfCmtsCmStatusValue."

REFERENCE

"Data-Over-Cable Service Interface Specifications: Radio Frequency Interface Specification SP-RFIV2.0-I10-051209, Section 11.2.

Data-Over-Cable Service Interface Specifications: Operations Support System Interface Specification SP-OSSIV2.0-I09-050812, Section 6.3.4.2.

Data-Over-Cable Service Interface Specifications DOCSIS 3.0 Operations Support System Interface Specification: CM-SP-OSSIV3.0-I05-071206."

7.2.4 UDP-MIB [RFC 4113]

DOCSIS 2.0 defines the use of the UDP MIB [RFC 2013]. This version of the MIB module has since been updated in [RFC 4113]. The DOCSIS 2.0 CM that supports IPv6 may implement [RFC 4113] per [OSSIV3.0]. The DOCSIS 2.0 CM that supports IPv6 may implement [RFC 2013] per [OSSIV2.0].

7.2.5 IGMP-STD-MIB [RFC 2933]

DOCSIS 2.0 requires the implementation of the IGMP-STD-MIB [RFC 2933]. This MIB only supports IGMPv2 multicast groups. When GMAC Explicit Multicast DSID Forwarding is enabled, the use of the IGMP-STD-MIB [RFC 2933] is not required.

7.2.6 DOCS-QOS-MIB [OSSIV2.0] and DOCS-QOS3-MIB [OSSIV3.0]

A DOCSIS 2.0+IPv6 CM is required to support the DOCS-QOS-MIB [OSSIV2.0]. DOCSIS 2.0+IPv6 CMs that support Upstream Drop Classifiers (UDCs) and IPv6 packet classification are required to support the MIB object definitions for the docsQosPktClassTable from DOCS-QOS3-MIB [OSSIV3.0] rather than the definitions for docsQosPktClassTable in DOCS-QOS-MIB [OSSIV2.0].

A DOCSIS 2.0+IPv6 CM that supports GMAC Explicit Multicast DSID Forwarding is required to support the following CM DSID MIB objects from the DOCS-QOS3-MIB [OSSIV3.0].

- docsQosCmDsidTable
 - docsQosCmDsidEntry
 - docsQosCmDsidDsid
 - docsQosCmDsidUsage
 - docsQosCmDsidCmInterfaceMask
 - docsQosCmDsidFwdCmInterfaceMask
- docsQosCmDsidClientTable
 - docsQosCmDsidClientEntry
 - docsQosCmDsidClientDsid
 - docsQosCmDsidClientClientMacId
 - docsQosCmDsidClientClientMacAddr

The DOCSIS 2.0+IPv6 CM that supports GMAC Explicit Multicast DSID Forwarding may implement the docsQosCmDsidStatsTable and if supported, the following objects are included:

- docsQosCmDsidStatsTable
 - docsQosCmDsidStatsEntry
 - docsQosCmDsidStatsDsid
 - docsQosCmDsidStatsNumPackets

The omitted columnar objects from the CmDsid tables identified above should return a “noSuchObject” when read by a SNMP Manager.

7.2.7 DOCS-BPI2-MIB [ID BPI+]

A DOCSIS 2.0+IPv6 CM is required to support the Internet Draft BPI+ MIB version 5.

7.3 DOCSIS Events

The DOCSIS 2.0+IPv6 CM is required to implement the events listed in Annex D [OSSIV2.0]. Some of the Event IDs occur in both [OSSIV2.0] and [OSSIV3.0]. An Event ID from [OSSIV3.0] listed below supersedes the same Event ID from [OSSIV2.0].

The following DHCP Event IDs from [OSSIV3.0] are required to be used when the DOCSIS 2.0+IPv6 CM is operating with an IPv4 Management Stack.

- 68000100
- 68000200
- 68000300
- 68000301

The following Event Ids from [OSSIV3.0] are required to be supported by the DOCSIS 2.0+IPv6 CM for support of IPv6 Management Stack.

- 68001200
- 68001201
- 68001202
- 68001203
- 68001301
- 68001302
- 68010500

The following Event Ids from [OSSIV3.0] are required to be supported by the DOCSIS 2.0+IPv6 CM that supports the optional APM or Dual Stack provisioning modes.

- 68010700
- 68001204
- 68001205

The following Event Ids from [OSSIV3.0] are required to be supported by the DOCSIS 2.0+IPv6 CM for support of IPv6 and IPv4 lease renewal events.

- 68010100
- 68010200
- 68010300
- 68010400
- 68010600

The following Event Ids from [OSSIV3.0] are required to be supported by the DOCSIS 2.0+IPv6 CM for support of ToD operations over IPv4 or IPv6.

- 68000403
- 68000404

The following Event Ids from [OSSIV3.0] are required to be supported by the DOCSIS 2.0+IPv6 CM for support of IPv6 and IPv4 software upgrade events.

- 69010100
- 69010200
- 69010300
- 69010400
- 69010500
- 69010600
- 69010700
- 69010800
- 69010900
- 69011000
- 69011100
- 69011200
- 69020100
- 69020200
- 69020300
- 69020400
- 69020500
- 69020600
- 69020700
- 69020800
- 69020900

7.4 SNMP Access Requirements

Support for both NmAccess and SNMP Coexistence is required for a DOCSIS 2.0+IPv6 CM with some changes. The SNMP access method Open Access defined in DOCSIS 2.0 is deprecated for the DOCSIS 2.0+IPv6 CM. When defining SNMP Coexistence parameters, the DOCSIS 2.0+IPv6 CM is required to support the enhancements to the SNMP Target Address Table defined in [RFC 3419]. The DOCSIS 2.0+IPv6 CM also is required to accept the new configuration file TLVs defined in [MULPIV3.0] and [OSSIV3.0] including the SNMPv3 Notification Receiver TLV. These new encodings allow for the configuration of IPv6 address in the SNMP Coexistence and SNMPv3 frameworks.

It is also important to note that NmAccess configurations settings in the CM config file do not allow for IPv6 addresses. As a result, if a DOCSIS 2.0+IPv6 CM receives a configuration file with NmAccess settings and is provisioned in any IPv6 provisioning mode, the DOCSIS 2.0+IPv6 CM may be unmanageable. When the DOCSIS 2.0+IPv6 CM is provisioned for IPv6, the SNMP Access method needs to be configured with SNMP Coexistence or SNMPv3 enabled.

If the DOCSIS 2.0+IPv6 CM receives a configuration file that does not contain any SNMP configuration TLVs, the DOCSIS 2.0+IPv6 CM will become unmanageable via SNMP after registration [OSSIV3.0]. The use of CMTS tools (e.g., Ranging Abort) to reset a modem will be needed to force the modem to re-initialize and acquire a new configuration file.

Configuration of NmAccess and Coexistence modes are accomplished through the CM configuration file TLVs. DOCSIS 2.0 CMs support the use of configuration TLVs defined in [RFIv2.0].

- SNMP Write-Access Control (TLV10)
- SNMP MIB Object (TLV 11)
- SnmpV3 Kickstart Value (TLV34)

In addition, the DOCSIS 2.0+IPv6 CM is required to support the following SNMP Configuration TLVs defined in [MULPIv3.0].

- SNMPv3 Notification Receiver (TLV 38)
- SNMPv1v2c Coexistence Configuration (TLV 53)
- SNMPv3 Access View Configuration (TLV 54)
- SNMP CPE Access Control (TLV55)

The configuration TLVs 53 and 54 allow the operator to configure community string and SNMP Coexistence tables in a highly efficient manner where TLV-11 has been used in DOCSIS 2.0. The DOCSIS 2.0+IPv6 CM is required to support the definition of TLV38 from MULPI in order to support the needed IPv6 transport and trap receiver encodings when the DOCSIS 2.0+IPv6 CM is provisioned with an IPv6 single or Dual Stack configuration. TLV 55 also provides an optimization to enable or disable SNMP Access from the CMCI ports.

8 CABLE MODEM SOFTWARE DOWNLOAD

The DOCSIS 2.0+IPv6 CM allows both SNMP-initiated and configuration-file-initiated software downloads over IPv6. The DOCSIS 2.0+IPv6 CM implements the docsDevSoftware group [RFC 4639] for the management and initiation of upgrades. The DOCSIS 2.0+IPv6 CM also supports the Software Upgrade IPv6 TFTP Server TLV (TLV 58) defined in [MULPIv3.0] for downloads triggered via the configuration file. For these downloads, the DOCSIS 2.0+IPv6 CM selects the software server as defined in the *Downloading Cable Modem Operating Software* section of [MULPIv3.0].

Appendix I DHCPv6 Options

The table below shows all of the DOCSIS defined DHCPv6 options used by a DOCSIS 2.0+IPv6 CM during IPv6 provisioning. Some of these options are specific to certain types of embedded implementations and are not required for all devices.

Table 1 - DHCPv6 Options

Option Number	Option Name	Reference
1	Client Identifier option (DUID)	[RFC 3315]
2	Server Identifier Option	[RFC 3315]
3	IA_NA option (IPv6 address)	[RFC 3315]
6	Option Request Option	[RFC 3315]
14	Rapid Commit Option	[RFC 3315]
16	Vendor Class	[RFC 3315]
19	Reconfigure Message option	[RFC 3315]
20	Reconfigure Accept Option	[RFC 3315]
17	Vendor-specific information option	
Option Number	Option Name	
1	CL Option Request option	[DHCP-REG]
32	TFTP Server Addresses option	[DHCP-REG]
33	Configuration File Name option	[DHCP-REG]
34	Syslog Server Addresses option	[DHCP-REG]
35	TLV5 Encoding	[DHCP-REG]
36	DOCSIS Device Identifier option	[DHCP-REG]
0x087A	CableLabs client configuration (Applicable only for eDOCSIS devices with eCM+eMTA)	[DHCP-REG]
37	Time Protocol Servers option	[DHCP-REG]
38	Time Offset option	[DHCP-REG]

Appendix II Acknowledgements

On behalf of the cable industry and our member companies, CableLabs would like to thank the following individuals for their contributions to the development of this Technical Report.

Contributor	Company Affiliation
John Brzozowski	Comcast
Jason Combs	Comcast
Eduardo Cardona	CableLabs
Margo Dolas	Broadcom
Chris Donley	CableLabs
Ralph Droms	Cisco Systems
Kirk Erichsen	Time Warner Cable
Brian Hedstrom	CableLabs
Deepak Kharbanda	CableLabs
Diego Mazzola	Texas Instruments
Lakshmi Raman	CableLabs
Karthik Sundaresan	CableLabs
Dan Torbet	ARRIS
Jason Weil	Cox
Greg White	CableLabs

We would particularly like to thank Margo Dolas (Broadcom) as the lead author for this Technical Report and for her work in numerous areas including IP Forwarding and Multicast. We would like to thank Dan Torbet (ARRIS) for all his efforts including his contribution to the CM Initialization and Management sections. We would like to thank Diego Mazzola (Texas Instruments) for his effort on the Provisioning, Multicast and Software Download sections. We would like to thank Ralph Droms (Cisco Systems) for his clarifications on the IPv6 protocol. We thank Deepak Kharbanda (CableLabs) who led the IPv6 Focus Team that developed this Technical Report. And finally, many thanks go out to all the active members of the IPv6 Focus Team who contributed to this Technical Report.