

OpenCable™ Specifications

Home Networking

OpenCable Home Networking MIB Specification

OC-SP-MIB-HN-I02-100507

ISSUED

Notice

This OpenCable specification is the result of a cooperative effort undertaken at the direction of Cable Television Laboratories, Inc. for the benefit of the cable industry and its customers. This document may contain references to other documents not owned or controlled by CableLabs. Use and understanding of this document may require access to such other documents. Designing, manufacturing, distributing, using, selling, or servicing products, or providing services, based on this document may require intellectual property licenses from third parties for technology referenced in this document.

Neither CableLabs nor any member company is responsible to any party for any liability of any nature whatsoever resulting from or arising out of use or reliance upon this document, or any document referenced herein. This document is furnished on an "AS IS" basis and neither CableLabs nor its members provides any representation or warranty, express or implied, regarding the accuracy, completeness, noninfringement, or fitness for a particular purpose of this document, or any document referenced herein.

© Copyright 2010 Cable Television Laboratories, Inc.
All rights reserved.

Document Status Sheet

Document Control Number:	OC-SP-MIB-HN-I02-100507			
Document Title:	OpenCable Home Networking MIB Specification			
Revision History:	I01 - 9/21/09			
	I02 - 5/7/10			
Date:	May 7, 2010			
Status:	Work in Progress	Draft	Issued	Closed
Distribution Restrictions:	Author Only	CL/Member	CL/Member/Vendor	Public

Key to Document Status Codes

- Work in Progress** An incomplete document, designed to guide discussion and generate feedback that may include several alternative requirements for consideration.
- Draft** A document in specification format considered largely complete, but lacking review by Members and vendors. Drafts are susceptible to substantial change during the review process.
- Issued** A stable document, which has undergone rigorous member and vendor review and is suitable for product design and development, cross-vendor interoperability, and for certification testing.
- Closed** A static document, reviewed, tested, validated, and closed to further engineering change requests to the specification through CableLabs.

Trademarks

CableLabs[®], DOCSIS[®], EuroDOCSIS[™], eDOCSIS[™], M-CMTS[™], PacketCable[™], EuroPacketCable[™], PCMM[™], CableHome[®], CableOffice[™], OpenCable[™], OCAP[™], CableCARD[™], M-Card[™], DCAS[™], tru2way[™], and CablePC[™] are trademarks of Cable Television Laboratories, Inc.

Contents

1	SCOPE	1
1.1	INTRODUCTION AND PURPOSE.....	1
1.2	REQUIREMENTS.....	1
2	REFERENCES	2
2.1	NORMATIVE REFERENCES.....	2
2.2	REFERENCE ACQUISITION.....	2
3	TERMS AND DEFINITIONS	3
4	ABBREVIATIONS AND ACRONYMS	3
5	OC-STB-HN-MIB	4
ANNEX A	MIB OBJECT REQUIREMENTS	44
APPENDIX I	OCHN MIB MAPS	50
I.1	OCHN TO MoCA MIB MAP.....	50
APPENDIX II	REVISION HISTORY	56

Tables

TABLE A-1	MIB IMPLEMENTATION SUPPORT.....	44
TABLE A-2	SNMP ACCESS REQUIREMENTS.....	44

This page left blank intentionally.

1 SCOPE

1.1 Introduction and Purpose

This specification defines the MIB requirements for OpenCable Host 2.x Home Networking Extension. The MIB, as defined here, will reside on the OpenCable Host device.

1.2 Requirements

Throughout this document, the words that are used to define the significance of particular requirements are capitalized. These words are:

"SHALL"	This word means that the item is an absolute requirement of this specification.
"SHALL NOT"	This phrase means that the item is an absolute prohibition of this specification.
"SHOULD"	This word means that there may exist valid reasons in particular circumstances to ignore this item, but the full implications should be understood and the case carefully weighed before choosing a different course.
"SHOULD NOT"	This phrase means that there may exist valid reasons in particular circumstances when the listed behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
"MAY"	This word means that this item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because it enhances the product, for example; another vendor may omit the same item.

2 REFERENCES

2.1 Normative References

In order to claim compliance with this specification, it is necessary to conform to the following standards and other works as indicated, in addition to the other requirements of this specification. Notwithstanding, intellectual property rights may be required to use or implement such normative references.

- [OCHD2.1] OpenCable Host Device 2.1 Core Functional Requirements, OC-SP-HOST2.1-CFR-I11-100507, May 7, 2010, Cable Television Laboratories, Inc.
- [RFC 2863] IETF RFC 2863, K. McCloghrie and F. Kastholz, The Interfaces Group MIB, June 2000.
- [RSD TECH] Reserved Services Domain Technology 1.0 Specification, OC-SP-RSD-TECH-I01-080630, June 30, 2008, Cable Television Laboratories, Inc.
- [RSD PROT] OpenCable Home Networking – Reserved Services Domain Protocols Specification, OC-SP-RSD-PROT-I01-080828, August 28, 2008, Cable Television Laboratories, Inc.
- [HN2.0] OpenCable Host Home Networking Extension 2.0, OC-SP-HOST-HN2.0-I04-100507, May 7, 2010, Cable Television Laboratories, Inc.

2.2 Reference Acquisition

- Cable Television Laboratories, Inc., 858 Coal Creek Circle, Louisville, CO 80027; Phone +1-303-661-9100; Fax +1-303-661-9199; <http://www.cablelabs.com>
- Internet Engineering Task Force, <http://www.ietf.org>

3 TERMS AND DEFINITIONS

This specification does not define any new terms and definitions.

4 ABBREVIATIONS AND ACRONYMS

This specification does not define any new abbreviations.

5 OC-STB-HN-MIB

```

OC-HOME-NETWORK-MIB DEFINITIONS ::= BEGIN

IMPORTS
    OBJECT-GROUP,
    MODULE-COMPLIANCE
        FROM SNMPv2-CONF                -- RFC 2580
    Integer32,
    Unsigned32,
    Counter32,
    OBJECT-TYPE,
    MODULE-IDENTITY
        FROM SNMPv2-SMI                -- RFC 2578
    TruthValue,
    RowStatus,
    MacAddress,
    TEXTUAL-CONVENTION
        FROM SNMPv2-TC                -- RFC 2579
    SnmpAdminString
        FROM SNMP-FRAMEWORK-MIB       -- RFC 3411
    InetAddressType,
    InetPortNumber,
    InetAddress
        FROM INET-ADDRESS-MIB         -- RFC 4001
    clabProjOpenCable
        FROM CLAB-DEF-MIB
    ifIndex
        FROM IF-MIB
    ;

ocHnMibModule MODULE-IDENTITY
    LAST-UPDATED "201005070000Z"        -- May 7, 2010
    ORGANIZATION "Cable Television Laboratories, Inc."
    CONTACT-INFO
        "Postal: Cable Television Laboratories, Inc.
         858 Coal Creek Circle
         Louisville, Colorado 80027-9750
         U.S.A.
         Phone:   +1 303-661-9100
         Fax:     +1 303-661-9199
         E-mail:  mibs@cablelabs.com"
    DESCRIPTION
        "This MIB module contains the objects for the
         management of an OpenCable Home Network. The
         MIB resides on the OpenCable Host Device if the
         Home Network Extension is implemented."
    REVISION "201005070000Z"           -- May 7, 2010
    DESCRIPTION
        "Added device properties group."
    REVISION "200909210000Z"           -- September 21, 2009
    DESCRIPTION
        "This version is being published as part of the
         OpenCable Home Networking MIB specification I01."
    ::= { clabProjOpenCable 2 }

Tenths ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d-1"
    STATUS      current
    DESCRIPTION
        "This data type represents generic decimal units
         in Tenths. For example, a value of 5.1 will be
         represented as 51."
    SYNTAX      Integer32

```

```

PowerUnit ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        "Represents a well-known RSD power unit of
        measurement."
    SYNTAX      INTEGER {
                    other(1),
                    dBmV(2),
                    dBm(3),
                    mW(4)
                }

--
-- Node definitions
--

ocHnNotifications OBJECT IDENTIFIER ::= { ocHnMibModule 1 }
ocHnMibObjects     OBJECT IDENTIFIER ::= { ocHnMibModule 2 }

ocHnHomeNetStatus OBJECT IDENTIFIER ::= { ocHnMibObjects 1 }

--
-- Reserved Services Domain Status
--

ocHnRsdManagerStatus OBJECT IDENTIFIER ::= { ocHnHomeNetStatus 1 }

ocHnRsdManagerImportanceNumber OBJECT-TYPE
    SYNTAX      Unsigned32 (0..255)
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Configurable importance number for the RSDManager in
        this device. Used to determine the preferred RSDManager
        on the home network."
    ::= { ocHnRsdManagerStatus 1 }

ocHnRsdManagerPreferredStatus OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "True indicates this is the preferred RSD Manager
        on the home network."
    ::= { ocHnRsdManagerStatus 2 }

--
-- UPnP Services Status information
--

ocHnDevUpnpServiceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnDevUpnpServiceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table defines each service offered
        by this device. One row should be created
        for each supported service."
    ::= { ocHnHomeNetStatus 2 }

ocHnDevUpnpServiceEntry OBJECT-TYPE
    SYNTAX      OcHnDevUpnpServiceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry defines a UPnP service."
    INDEX { ocHnDevUpnpServiceIndex }

```

```

 ::= { ocHnDevUpnpServiceTable 1 }

OcHnDevUpnpServiceEntry ::=
  SEQUENCE {
    ocHnDevUpnpServiceIndex
      Unsigned32,
    ocHnDevUpnpServiceType
      INTEGER,
    ocHnDevUpnpServiceAvailable
      TruthValue
  }

ocHnDevUpnpServiceIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "Table Index."
  ::= { ocHnDevUpnpServiceEntry 1 }

ocHnDevUpnpServiceType OBJECT-TYPE
  SYNTAX      INTEGER {
    cds(1),
    srs(2),
    qosManager(3),
    qosDevice(4),
    qosPolicyHolder(5),
    avt(6),
    cm(7),
    rcs(8)
  }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "Service options currently available."
  ::= { ocHnDevUpnpServiceEntry 2 }

ocHnDevUpnpServiceAvailable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "Service is available (true) or unavailable (false)."
  ::= { ocHnDevUpnpServiceEntry 3 }

--
-- Supported Channels Table
--

ocHnDevSupportedChannelTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF OcHnDevSupportedChannelEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table identifies the RSD Technology channels
    for each interface supported by a particular RSD node.
    This table is required for RF-based technologies."
  ::= { ocHnHomeNetStatus 3 }

ocHnDevSupportedChannelEntry OBJECT-TYPE
  SYNTAX      OcHnDevSupportedChannelEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "Each entry defines an offered channel by interface."
  INDEX { ifIndex, ocHnDevSupportedChannelIndex }
  ::= { ocHnDevSupportedChannelTable 1 }

```

```

OcHnDevSupportedChannelEntry ::=
    SEQUENCE {
        ocHnDevSupportedChannelIndex
            Unsigned32,
        ocHnDevSupportedChannelLastOperatingFreq
            TruthValue,
        ocHnDevSupportedChannelInUse
            TruthValue,
        ocHnDevSupportedChannelFrequency
            Unsigned32,
        ocHnDevSupportedChannelEligible
            TruthValue
    }

ocHnDevSupportedChannelIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Index for each channel supported by the
         interface indicated by the ifIndex."
    ::= { ocHnDevSupportedChannelEntry 1 }

ocHnDevSupportedChannelLastOperatingFreq OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates this channel/frequency
         was tuned when last in the LinkUp state.
         The value is persistent through reboots."
    ::= { ocHnDevSupportedChannelEntry 2 }

ocHnDevSupportedChannelInUse OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This channel is currently being used by
         this interface."
    ::= { ocHnDevSupportedChannelEntry 3 }

ocHnDevSupportedChannelFrequency OBJECT-TYPE
    SYNTAX      Unsigned32 (0..2000000000)
    UNITS       "hertz"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Channel center frequency. This channel must be available
         for selection as the operating frequency."
    ::= { ocHnDevSupportedChannelEntry 4 }

ocHnDevSupportedChannelEligible OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This channel is currently eligible for use."
    ::= { ocHnDevSupportedChannelEntry 5 }

--
-- Device Properties: Lists various UPnP Device properties
--

ocHnDevProperties OBJECT IDENTIFIER ::= { ocHnHomeNetStatus 4 }

```

```

ocHnDevPropertiesFriendlyName OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Value from the <friendlyName> element in the OCAP Root
        Device Description of the device as defined in Annex A
        of [HNP2.0]."
```

::= { ocHnDevProperties 1 }

```

--
-- Rotameter configuration options
--

ocHnROConfiguration OBJECT IDENTIFIER ::= { ocHnMibObjects 2 }
```

ocHnRotameterConfigTable OBJECT-TYPE

```

    SYNTAX      SEQUENCE OF OcHnRotameterConfigEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains the basic rotameter observation
        configuration parameters. Each row defines a set of
        parameters to configure a rotameter observation. The
        device may obtain per stream statistics, if requested,
        using one or more rows in the
        PerStreamRotameterConfigTable."
```

::= { ocHnROConfiguration 1 }

ocHnRotameterConfigEntry OBJECT-TYPE

```

    SYNTAX      OcHnRotameterConfigEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry represents set of configuration parameters for
        one observation."
```

INDEX { ocHnRotameterConfigIndex }

::= { ocHnRotameterConfigTable 1 }

OcHnRotameterConfigEntry ::=

```

    SEQUENCE {
        ocHnRotameterConfigIndex
            Unsigned32,
        ocHnRotameterConfigRowStatus
            RowStatus,
        ocHnRotameterConfigObservationActive
            TruthValue,
        ocHnRotameterConfigPeriod
            Unsigned32,
        ocHnRotameterConfigMonitorResolutionPeriod
            Unsigned32,
        ocHnRotameterConfigQosSegmentId
            OCTET STRING,
        ocHnRotameterConfigEndpointMacAddress
            MacAddress
    }
```

ocHnRotameterConfigIndex OBJECT-TYPE

```

    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table Index."
```

::= { ocHnRotameterConfigEntry 1 }

ocHnRotameterConfigRowStatus OBJECT-TYPE

```

    SYNTAX      RowStatus
```

```

MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "Controls and reflects the status of rows in this
    Table (see RowStatus textual convention). There
    is no restriction on changing any of the associated
    columns for this row while this object is set
    to active (i.e., columnar objects can be modified
    when the row is active). An active row does not
    equate to an active observation; it implies only that
    the rotameter observation can be initiated when
    ocHnRotameterConfigObservationActive is set to 'True'."
 ::= { ocHnRotameterConfigEntry 2 }

ocHnRotameterConfigObservationActive OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "Setting this value to 'True' causes the rotameter to be
    configured and activated per the specified columns in
    the row. Only one row observation can be active at any
    given time."
 ::= { ocHnRotameterConfigEntry 3 }

ocHnRotameterConfigPeriod OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "This integer field specifies the duration in seconds
    over which the Rotameter Observation is performed.
    This value must be less than or equal to the Monitoring
    Resolution Period. The default is 0 and indicates no
    monitoring."
 ::= { ocHnRotameterConfigEntry 4 }

ocHnRotameterConfigMonitorResolutionPeriod OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "This integer field specifies, in seconds, how often a
    Rotameter observation is initiated. The default value
    of 0 indicates no monitoring in progress."
 ::= { ocHnRotameterConfigEntry 5 }

ocHnRotameterConfigQosSegmentId OBJECT-TYPE
SYNTAX OCTET STRING
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "This uniquely identifies a network segment of a shared
    Media technology. This parameter needs
    to be configured to obtain traffic statistics for a
    specific QosSegment and for a specific traffic stream
    identified by a combination of Layer2StreamId and a
    QosSegmentId. The default value of 0 indicates no
    QosSegment is specified."
 ::= { ocHnRotameterConfigEntry 6 }

ocHnRotameterConfigEndpointMacAddress OBJECT-TYPE
SYNTAX MacAddress
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "This is an optional field. If value of all zeros is

```

```

        provided, the device reports information about the traffic
        for the entire QosSegment identified by QosSegmentId.
        If non-zero value is provided, this device provides
        information about traffic between its interface, identified
        by the ocHnQosROStatsMacAddress field and the device,
        identified by this parameter. If no value is specified,
        the device either reports traffic to/from itself or between
        itself and other devices on the network."
 ::= { ocHnRotameterConfigEntry 7 }

--
-- Rotameter augmentation table
-- Use in conjunction with the OcHnRotameterConfigTable if
-- stream-based observations are required
--

ocHnPerStreamRotameterConfigTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnPerStreamRotameterConfigEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table optionally augments the rotameter observation
        configuration parameters. Each row defines a set of
        parameters to configure a per-stream rotameter observation.
        Care must be taken when specifying both
        ocHnPerStreamRotameterConfigTrafficHandle and
        ocHnPerStreamRotameterConfigLayer2StreamId parameters to
        ensure that they both identify the same traffic stream."
 ::= { ocHnROConfiguration 2 }

ocHnPerStreamRotameterConfigEntry OBJECT-TYPE
    SYNTAX      OcHnPerStreamRotameterConfigEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry represents one stream traffic descriptor."
    INDEX { ocHnPerStreamRotameterConfigIndex, ocHnRotameterConfigIndex }
 ::= { ocHnPerStreamRotameterConfigTable 1 }

OcHnPerStreamRotameterConfigEntry ::=
    SEQUENCE {
        ocHnPerStreamRotameterConfigIndex
            Unsigned32,
        ocHnPerStreamRotameterConfigRowStatus
            RowStatus,
        ocHnPerStreamRotameterConfigLayer2StreamId
            OCTET STRING,
        ocHnPerStreamRotameterConfigTrafficHandle
            OCTET STRING,
        ocHnPerStreamRotameterConfigObservationActive
            TruthValue
    }

ocHnPerStreamRotameterConfigIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table Index."
 ::= { ocHnPerStreamRotameterConfigEntry 1 }

ocHnPerStreamRotameterConfigRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Controls and reflects the status of rows in this

```

```

        table (see RowStatus textual convention). There
        is no restriction on changing any of the associated
        columns for this row while this object is set
        to active (i.e., columnar objects can be modified
        when the row is active).
 ::= { ocHnPerStreamRotameterConfigEntry 2}

ocHnPerStreamRotameterConfigLayer2StreamId OBJECT-TYPE
SYNTAX      OCTET STRING (SIZE (64) )
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "This identifies a unique traffic stream flowing through a
    QoS segment identified by a QosSegmentId. A Control Point
    optionally specifies this field if it is interested in
    obtaining information for a specific traffic stream
    identified by a Layer2StreamId on the specified
    QosSegmentId. The default value of '0x00' indicates
    no ocHnRotameterLayer2StreamId specified."
 ::= { ocHnPerStreamRotameterConfigEntry 3 }

ocHnPerStreamRotameterConfigTrafficHandle OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "This identifies a unique UPnP traffic stream flowing
    through a device that supports a QosDevice service.
    A Control Point optionally specifies this field if it is
    interested in obtaining information for a specific UPnP
    traffic stream. The default value 'null' indicates
    no handle has been specified."
 ::= { ocHnPerStreamRotameterConfigEntry 4 }

ocHnPerStreamRotameterConfigObservationActive OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "Setting this value to 'True' causes the rotameter to be
    configured per the specified columns in the row. Multiple
    rows in this table may be active concurrently to allow for
    multiple streams to be included in a single observation."
 ::= { ocHnPerStreamRotameterConfigEntry 5 }

ocHnQos OBJECT IDENTIFIER ::= { ocHnMibObjects 3 }

--
-- QoS stream, policy, and traffic configuration
-- for RSD Technologies only.

--
-- Dynamic configuration parameters
--

ocHnQosTrafficInfo OBJECT IDENTIFIER ::= { ocHnQos 1 }

ocHnQosStreamsInfoCollectionTrigger OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "Setting to true(1) causes this device
    to populate the ocHnQosTrafficDescTable with traffic
    descriptor information for each known stream established
    using UPnP QoS."
 ::= { ocHnQosTrafficInfo 1 }

```

```

--
-- QoS traffic descriptor table. Populated only when triggered
-- by setting the ocHnQosStreamsInfoCollectionTrigger to true(1).
--

ocHnQosTrafficDescTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnQosTrafficDescEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains the traffic descriptor information
        for each traffic stream established using UPnP QoS. It is
        populated only when directed to do so via the MIB object
        ocHnQosStreamsInfoCollectionTrigger. Each invocation of
        the collection trigger will cause a refresh
        of these values."
    ::= { ocHnQosTrafficInfo 2 }

ocHnQosTrafficDescEntry OBJECT-TYPE
    SYNTAX      OcHnQosTrafficDescEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry represents one stream traffic descriptor."
    INDEX { ocHnQosTrafficDescIndex }
    ::= { ocHnQosTrafficDescTable 1 }

OcHnQosTrafficDescEntry ::=
    SEQUENCE {
        ocHnQosTrafficDescIndex
            Unsigned32,
        ocHnQosTrafficHandle
            OCTET STRING,
        ocHnQosTrafficQDMacAddress
            MacAddress,
        ocHnQosTrafficNetworkAddressType
            InetAddressType,
        ocHnQosTrafficSourceAddress
            InetAddress,
        ocHnQosTrafficSourcePort
            InetPortNumber,
        ocHnQosTrafficDestinationAddress
            InetAddress,
        ocHnQosTrafficDestinationPort
            InetPortNumber,
        ocHnQosTrafficIpProtocol
            Unsigned32,
        ocHnQosTrafficV3TrafficIdSourceUuid
            OCTET STRING,
        ocHnQosTrafficV3TrafficIdDestinationUuid
            OCTET STRING,
        ocHnQosTrafficMediaServerConnectionId
            Integer32,
        ocHnQosTrafficMediaRendererConnectionId
            Integer32,
        ocHnQosTrafficLeaseTime
            Unsigned32,
        ocHnQosTrafficCritical
            INTEGER,
        ocHnQosTrafficUserName
            SnmpAdminString,
        ocHnQosTrafficVendorApplicationName
            OCTET STRING,
        ocHnQosTrafficPortName
            OCTET STRING,
        ocHnQosTrafficServiceProviderServiceName
    }

```

```

        OCTET STRING,
        ocHnQoSTrafficCpName
        SnmpAdminString
    }

ocHnQoSTrafficDescIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table Index."
    ::= { ocHnQoSTrafficDescEntry 1 }

ocHnQoSTrafficHandle OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The unique identifier associated with a particular
        instance of TrafficDescriptor (i.e., a particular
        traffic stream). This object serves as a secondary
        index into the related TSPEC table in which the active
        TSPEC is denoted."
    ::= { ocHnQoSTrafficDescEntry 2 }

ocHnQoSTrafficQDMacAddress OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Identifies a QoS Device in which the QoS
        Stream/flow was registered."
    ::= { ocHnQoSTrafficDescEntry 3 }

ocHnQoSTrafficNetworkAddressType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "IP Address type for source and destination IP
        addresses in the traffic descriptors.
        Textual convention will report IPv4(1) or
        IPv6(2).".
    ::= { ocHnQoSTrafficDescEntry 4 }

ocHnQoSTrafficSourceAddress OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Source IP address in traffic descriptor. A value
        of 0.0.0.0 (:: for IPv6) indicates 'do not care'. This must
        be consistent with the object
        ocHnQoSTrafficNetworkAddressType within a conceptual row."
    ::= { ocHnQoSTrafficDescEntry 5 }

ocHnQoSTrafficSourcePort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Source protocol port number in traffic descriptor.
        A value of 0 represents a 'Don't Care', i.e., the
        condition where a Control Point wants to set up
        QoS for all traffic streams irrespective of the
        SourcePort."
    ::= { ocHnQoSTrafficDescEntry 6 }

```

```

ocHnQoSTrafficDestinationAddress OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Destination IP address in traffic descriptor. A value
        of 0.0.0.0 (:: for IPv6) indicates 'do not care'. This
        must be consistent with the object
        ocHnQoSTrafficNetworkAddressType."
    ::= { ocHnQoSTrafficDescEntry 7 }

ocHnQoSTrafficDestinationPort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Destination protocol port number in traffic descriptor.
        A value of 0 represents a 'Don't Care', i.e., the
        condition where a Control Point wants to set up
        QoS for all traffic streams irrespective of the
        DestinationPort."
    ::= { ocHnQoSTrafficDescEntry 8 }

ocHnQoSTrafficIpProtocol OBJECT-TYPE
    SYNTAX      Unsigned32 (0..255)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "IP protocol number in traffic descriptor. A value
        of '0' represents a 'don't care' and the CP wants to set up
        QoS for traffic streams irrespective of the IpProtocol."
    ::= { ocHnQoSTrafficDescEntry 9 }

ocHnQoSTrafficV3TrafficIdSourceUuid OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Contains the UDN of the UPnP Device at the source. The
        UUID consists of the UDN of the device, including the
        prefix 'uuid:'."
    ::= { ocHnQoSTrafficDescEntry 10 }

ocHnQoSTrafficV3TrafficIdDestinationUuid OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Contains the UDN of the UPnP Device at the destination.
        The UUID consists of the UDN of the device, including
        the prefix 'uuid:'."
    ::= { ocHnQoSTrafficDescEntry 11 }

ocHnQoSTrafficMediaServerConnectionId OBJECT-TYPE
    SYNTAX      Integer32 (-1..65534)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Identifies the traffic stream established by
        the UPnP-AV Control Point at the DMS for which
        QoS is requested."
    ::= { ocHnQoSTrafficDescEntry 12 }

ocHnQoSTrafficMediaRendererConnectionId OBJECT-TYPE
    SYNTAX      Integer32 (-1..65534)
    MAX-ACCESS  read-only

```

```

STATUS      current
DESCRIPTION
    "Identifies the traffic stream established by the
    UPnP-AV Control Point at the DMR for which
    QoS is requested."
 ::= { ocHnQoSTrafficDescEntry 13 }

ocHnQoSTrafficLeaseTime OBJECT-TYPE
SYNTAX      Unsigned32
UNITS       "seconds"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "This object contains the lease time associated
    with a particular traffic stream. When not specified
    (which MUST only occur for prioritized streams), it
    indicates an indefinite lease, i.e., the
    TrafficDescriptor will remain active until it is
    explicitly removed or the QoSDevice is rebooted. The value
    reported in this object represents the remaining
    lease time. A NULL must be returned if this object
    is not populated."
 ::= { ocHnQoSTrafficDescEntry 14 }

ocHnQoSTrafficCritical OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value expresses the control point's belief on whether
    this traffic stream is critical. Streams for entertainment
    are not critical traffic streams. Examples of critical
    traffic streams are emergency alerts, emergency calls, etc.
    A NULL must be returned if this object is not populated."
 ::= { ocHnQoSTrafficDescEntry 15 }

ocHnQoSTrafficUserName OBJECT-TYPE
SYNTAX      SnmpAdminString (SIZE (0..64))
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Contains a string associated with the user who requested
    a particular traffic stream. This field identifies the name
    of the user initiating the UPnP-QoS Action."
 ::= { ocHnQoSTrafficDescEntry 16 }

ocHnQoSTrafficVendorApplicationName OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value contains a single URI string associated with an
    application. This field identifies the name of the
    application initiating the UPnP-QoS Action. For
    applications specified by vendors, the value of this
    field MUST begin with 'urn:1', followed by an ICANN domain
    name owned by the vendor, followed by
    ':application:', followed by an application name.
    A NULL must be returned if this object is not populated."
 ::= { ocHnQoSTrafficDescEntry 17 }

ocHnQoSTrafficPortName OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value contains a single URI string associated

```

```

        with the fixed port used by an application for its protocol
        set-up. This field, if present, shall identify the port
        number used by the application. The value of this field
        MUST begin with 'urn:', followed by an ICANN domain name
        owned by the vendor, followed by ':port:', followed by the
        port name. A NULL must be returned
        if this object is not populated."
 ::= { ocHnQoSTrafficDescEntry 18 }

ocHnQoSTrafficServiceProviderServiceName OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value contains a single URI string associated
    with a service offered by a service provider. This field
    identifies the name of the service offered by a service
    provider. For services provided by service providers, the
    value of this field MUST begin with 'urn:', followed by an
    ICANN domain name owned by a service provider, followed
    by ':service:', followed by a service name.
    A NULL must be returned if this object is not populated."
 ::= { ocHnQoSTrafficDescEntry 19 }

ocHnQoSTrafficCpName OBJECT-TYPE
SYNTAX      SnmpAdminString
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value is a string associated with the Control Point
    Requesting QoS for the traffic stream. This field
    identifies the name of the Control Point initiating the
    UPnP-QoS Action. A NULL must be returned if this object
    is not populated."
 ::= { ocHnQoSTrafficDescEntry 20 }

--
-- TSpec table. Populated only when triggered
-- by setting the ocHnQoSStreamsInfoCollectionTrigger to true(1).
--

ocHnQoStSpecTable OBJECT-TYPE
SYNTAX      SEQUENCE OF OcHnQoStSpecEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "This table contains the Traffic Specification (TSPEC)
    list. Each row represents a set of parameters that define
    the characteristics of the traffic stream. The TSPEC defines
    the resource requirements for carrying the traffic stream."
 ::= { ocHnQoSTrafficInfo 3 }

ocHnQoStSpecEntry OBJECT-TYPE
SYNTAX      OcHnQoStSpecEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "Each entry represents one stream traffic descriptor."
INDEX { ocHnQoStSpecTableIndex, ocHnQoSTrafficHandle }
 ::= { ocHnQoStSpecTable 1 }

OcHnQoStSpecEntry ::=
SEQUENCE {
    ocHnQoStSpecTableIndex
        Unsigned32,
    ocHnQoStSpec
        Unsigned32,

```

```

    ocHnQosActiveTspec
        TruthValue,
    ocHnQosTspecTrafficClass
        INTEGER,
    ocHnQosTspecReqQosType
        INTEGER,
    ocHnQosTspecDataRate
        Unsigned32,
    ocHnQosTspecPeakDataRate
        Unsigned32,
    ocHnQosTspecMaxBurstSize
        Unsigned32,
    ocHnQosTspecMaxPacketSize
        Unsigned32,
    ocHnQosTspecE2EMaxDelayHigh
        Unsigned32,
    ocHnQosTspecE2EMaxJitter
        Unsigned32
    }

ocHnQosTspecTableIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table Index. The unique TrafficHandle serves as a
        Secondary index into this table. This allows the
        Network manager to view all the TSPECs associated with
        a given TrafficHandle."
    ::= { ocHnQosTspecEntry 1 }

ocHnQosTspec OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of Tspec reflects the order of preference.
        TspecIndex values need not be
        consecutive numbers."
    ::= { ocHnQosTspecEntry 2 }

ocHnQosActiveTspec OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Only one Tspec can be active for a specific TrafficHandle.
        'True' signifies the entry is active. 'False' implies the
        Tspec can potentially be utilized."
    ::= { ocHnQosTspecEntry 3 }

ocHnQosTspecTrafficClass OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),
        networkControl(2),
        streamingControl(3),
        voice(4),
        av(5),
        data(6),
        audio(7),
        image(8),
        background(9),
        gaming(10)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION

```

```

        "Contains the traffic class associated with
        the traffic stream."
 ::= { ocHnQoSKeySpecEntry 4 }

ocHnQoSKeySpecReqQosType OBJECT-TYPE
    SYNTAX      INTEGER {
                    prioritized(1),
                    hybrid(2),
                    parameterized(3)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Specifies the type of Quality of Service
        that is requested with this traffic descriptor."
 ::= { ocHnQoSKeySpecEntry 5 }

ocHnQoSKeySpecDataRate OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This value intends to characterize the
        long term data rate."
 ::= { ocHnQoSKeySpecEntry 6 }

ocHnQoSKeySpecPeakDataRate OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Defines an upper bound on the data rate at which this
        traffic stream needs to be served in order to serve the
        traffic stream within time. If not provided, the default
        is the ocHnQoSTrafficTspecDataRate."
 ::= { ocHnQoSKeySpecEntry 7 }

ocHnQoSTspecMaxBurstSize OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Maximum burst size. A value of zero indicates
        a constant bit rate with no bursts."
 ::= { ocHnQoSTspecEntry 8 }

ocHnQoSTspecMaxPacketSize OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "bytes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Conveys the information about packetization of traffic
        streams by an application. The packet size includes the
        application data and an approximation of the overhead
        of all protocol headers at and above the IP layer.
        The default is 1500 if not specified."
 ::= { ocHnQoSTspecEntry 9 }

ocHnQoSTspecE2EMaxDelayHigh OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "microseconds"
    MAX-ACCESS  read-only
    STATUS      current

```

```

DESCRIPTION
    "Specifies the desired upper bound of the End-to-End
    Delay of individual packets belonging to the traffic
    stream."
 ::= { ocHnQoSspecEntry 10 }

ocHnQoSspecE2EMaxJitter OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "microseconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Specifies an UPPER bound to the End-to-End Jitter."
 ::= { ocHnQoSspecEntry 11 }

--
-- Policy table - One row is created
-- for each TLV 56 (RSD Configuration TLV)
--

ocHnQoSPolicyTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnQoSPolicyEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains the operator and user-created
        policies for the management of QoS for applications."
 ::= { ocHnQoS 2 }

ocHnQoSPolicyEntry OBJECT-TYPE
    SYNTAX      OcHnQoSPolicyEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry represents one QoS policy."
    INDEX { ocHnQoSPolicyRuleIdentifier }
 ::= { ocHnQoSPolicyTable 1 }

OcHnQoSPolicyEntry ::=
    SEQUENCE {
        ocHnQoSPolicyRuleIdentifier
            Unsigned32,
        ocHnQoSPolicyRowStatus
            RowStatus,
        ocHnQoSPolicyIpAddressType
            InetAddressType,
        ocHnQoSPolicySourceAddressUpLimit
            InetAddress,
        ocHnQoSPolicySourceAddressLowLimit
            InetAddress,
        ocHnQoSPolicySourcePortUpLimit
            InetPortNumber,
        ocHnQoSPolicySourcePortLowLimit
            InetPortNumber,
        ocHnQoSPolicyDestinationAddressUpLimit
            InetAddress,
        ocHnQoSPolicyDestinationAddressLowLimit
            InetAddress,
        ocHnQoSPolicyDestinationPortUpLimit
            InetPortNumber,
        ocHnQoSPolicyDestinationPortLowLimit
            InetPortNumber,
        ocHnQoSPolicyIpProtocolUpLimit
            Unsigned32,
        ocHnQoSPolicyIpProtocolLowLimit
            Unsigned32,
        ocHnQoSPolicyTrafficClass
    }

```

```

        INTEGER,
        ocHnQosPolicyPeakDataRateUpLimit
            Unsigned32,
        ocHnQosPolicyPeakDataRateLowLimit
            Unsigned32,
        ocHnQosPolicyMeanDataRateUpLimit
            Unsigned32,
        ocHnQosPolicyMeanDataRateLowLimit
            Unsigned32,
        ocHnQosPolicyMaxBurstSizeUpLimit
            Unsigned32,
        ocHnQosPolicyMaxBurstSizeLowLimit
            Unsigned32,
        ocHnQosPolicyE2EMaxDelayHighLimit
            Unsigned32,
        ocHnQosPolicyE2EMaxDelayLowLimit
            Unsigned32,
        ocHnQosPolicyBoundaryAddressType
            InetAddressType,
        ocHnQosPolicyBoundarySourceAddressUpLimit
            InetAddress,
        ocHnQosPolicyBoundarySourceAddressLowLimit
            InetAddress,
        ocHnQosPolicyBoundaryDestinationAddressUpLimit
            InetAddress,
        ocHnQosPolicyBoundaryDestinationAddressLowLimit
            InetAddress,
        ocHnQosPolicyUserName
            SnmpAdminString,
        ocHnQosPolicyVendorApplicationName
            SnmpAdminString,
        ocHnQosPolicyPortName
            SnmpAdminString,
        ocHnQosPolicyServiceProviderServiceName
            SnmpAdminString,
        ocHnQosPolicyCriticalFlag
            TruthValue,
        ocHnQosPolicyRequestedQosType
            INTEGER,
        ocHnQosPolicyStartTime
            Unsigned32,
        ocHnQosPolicyEndTime
            Unsigned32,
        ocHnQosPolicyTrafficLeaseTimeUpValue
            Unsigned32,
        ocHnQosPolicyTrafficLeaseTimeLowValue
            Unsigned32,
        ocHnQosPolicyRuleType
            INTEGER,
        ocHnQosPolicyRulePriority
            Unsigned32,
        ocHnQosPolicyTrafficImportanceNumber
            Unsigned32,
        ocHnQosPolicyUserImportanceNumber
            Unsigned32
    }

ocHnQosPolicyRuleIdentifier OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65535)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Unique identifier for each policy."
    ::= { ocHnQosPolicyEntry 1 }

ocHnQosPolicyRowStatus OBJECT-TYPE
    SYNTAX      RowStatus

```

```

MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "Controls and reflects the status of rows in this
    Table (see RowStatus textual convention). There
    is no restriction on changing any of the associated
    columns for this row while this object is set
    to active (i.e., columnar objects can be modified
    when the row is active)."
 ::= { ocHnQosPolicyEntry 2 }

ocHnQosPolicyIpAddressType OBJECT-TYPE
SYNTAX InetAddressType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "IPv4 or IPv6. Textual convention will
    report IPv4(1) or IPv6(2) This Type applies
    to all IP addresses in this row."
 ::= { ocHnQosPolicyEntry 3 }

ocHnQosPolicySourceAddressUpLimit OBJECT-TYPE
SYNTAX InetAddress
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The upper limit for source of traffic stream(s)
    for which a QoS Policy rule is applied. Default
    value for this field is of all ones
    (255.255.255.255 for IPv4 and
    ffff:ffff:ffff:ffff:ffff:ffff:ffff:ffff: for IPv6),
    and it represents that no upper limit is specified for
    the Source IP address."
 ::= { ocHnQosPolicyEntry 4 }

ocHnQosPolicySourceAddressLowLimit OBJECT-TYPE
SYNTAX InetAddress
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "Identifies the lower limit for source of traffic stream(s)
    for which a QoS Policy rule is applied. A default value for
    this field is all zeros (0.0.0.0 for IPv4 and :: for IPv6),
    and it represents that no lower limit is specified for the
    Source IP Address."
 ::= { ocHnQosPolicyEntry 5 }

ocHnQosPolicySourcePortUpLimit OBJECT-TYPE
SYNTAX InetPortNumber
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "Specifies the upper limit for port of source of traffic
    stream(s) for which a QoS Policy rule is applied. A default
    value for this field is 65535, and it represents that no
    upper limit is specified for the Source Port."
 ::= { ocHnQosPolicyEntry 6 }

ocHnQosPolicySourcePortLowLimit OBJECT-TYPE
SYNTAX InetPortNumber
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "Specifies the lower limit for port of source of traffic
    stream(s) for which a QoS Policy rule is applied. A default
    value for this field is 0, and it represents that no
    lower limit is specified for the Source Port."

```

```

 ::= { ocHnQosPolicyEntry 7 }

ocHnQosPolicyDestinationAddressUpLimit OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The upper limit for destination of traffic stream(s)
        for which a QoS Policy rule is applied. Default
        value for this field is of all ones
        (255.255.255.255 for IPv4 and
        ffff:ffff:ffff:ffff:ffff:ffff:ffff:ffff: for IPv6),
        and it represents that no upper limit is specified for
        the destination IP address."
 ::= { ocHnQosPolicyEntry 8 }

ocHnQosPolicyDestinationAddressLowLimit OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Identifies the lower limit for destination of traffic
        stream(s) for which a QoS Policy rule is applied. A default
        value for this field is all zeros (0.0.0.0 for IPv4
        and :: for IPv6), and it represents that no lower limit
        is specified for the destination IP Address."
 ::= { ocHnQosPolicyEntry 9 }

ocHnQosPolicyDestinationPortUpLimit OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the upper limit for port of destination of
        traffic stream(s) for which a QoS Policy rule is applied.
        A default value for this field is 65535, and it represents
        that no upper limit is specified for the destination Port."
 ::= { ocHnQosPolicyEntry 10 }

ocHnQosPolicyDestinationPortLowLimit OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the lower limit for port of destination of
        traffic stream(s) for which a QoS Policy rule is applied.
        A default value for this field is 0, and it represents that
        no lower limit is specified for the destination Port."
 ::= { ocHnQosPolicyEntry 11 }

ocHnQosPolicyIpProtocolUpLimit OBJECT-TYPE
    SYNTAX      Unsigned32 (0..255)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies an IANA-assigned upper limit for IP protocol
        number of traffic stream(s) for which a QoS Policy rule is
        applied. A default value for this field is 255, and it
        represents that no upper limit is specified for the
        IP Protocol."
 ::= { ocHnQosPolicyEntry 12 }

ocHnQosPolicyIpProtocolLowLimit OBJECT-TYPE
    SYNTAX      Unsigned32 (0..255)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION

```

```

        "Specifies an IANA-assigned lower limit for IP protocol
        number of traffic stream(s) for which a QoS Policy rule is
        applied. A default value for this field is 0, and it
        represents that no lower limit is specified for the
        IP Protocol."
 ::= { ocHnQosPolicyEntry 13 }

ocHnQosPolicyTrafficClass OBJECT-TYPE
    SYNTAX      INTEGER {
        networkControl(0),
        streamingControl(1),
        voice(2),
        av(3),
        data(4),
        audio(5),
        image(6),
        gaming(7),
        other(8),
        background(9)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the traffic class associated with traffic
        stream(s) for which a QoS Policy rule is applied."
 ::= { ocHnQosPolicyEntry 14 }

ocHnQosPolicyPeakDataRateUpLimit OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the upper limit for PeakDataRate of traffic
        stream(s) for which a QoS Policy rule is applied."
 ::= { ocHnQosPolicyEntry 15 }

ocHnQosPolicyPeakDataRateLowLimit OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the lower limit for PeakDataRate of traffic
        stream(s) for which a QoS Policy rule is applied."
 ::= { ocHnQosPolicyEntry 16 }

ocHnQosPolicyMeanDataRateUpLimit OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the upper limit for MeanDataRate of traffic
        stream(s) for which a QoS Policy rule is applied."
 ::= { ocHnQosPolicyEntry 17 }

ocHnQosPolicyMeanDataRateLowLimit OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the lower limit for MeanDataRate of traffic
        stream(s) for which a QoS Policy rule is applied."
 ::= { ocHnQosPolicyEntry 18 }

```

```

ocHnQosPolicyMaxBurstSizeUpLimit OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the upper limit for MaxBurstSize of traffic
        stream(s) for which a QoS Policy rule is applied."
    ::= { ocHnQosPolicyEntry 19 }

ocHnQosPolicyMaxBurstSizeLowLimit OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets/sec"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the lower limit for MaxBurstSize of traffic
        stream(s) for which a QoS Policy rule is applied."
    ::= { ocHnQosPolicyEntry 20 }

ocHnQosPolicyE2EMaxDelayHighLimit OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "microseconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the upper limit of E2EMaxDelayHigh
        (End-to-end delay) parameter for traffic stream(s) for
        which a QoS Policy rule is applied."
    ::= { ocHnQosPolicyEntry 21 }

ocHnQosPolicyE2EMaxDelayLowLimit
    OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "microseconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the lower limit of E2EMaxDelayLow
        (End-to-end delay) parameter for
        traffic stream(s) for which a QoS Policy rule is applied."
    ::= { ocHnQosPolicyEntry 22 }

ocHnQosPolicyBoundaryAddressType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "IPv4 or IPv6. Textual convention will
        report IPv4(1) or IPv6(2). This Type applies
        to all IP addresses in this row."
    ::= { ocHnQosPolicyEntry 23 }

ocHnQosPolicyBoundarySourceAddressUpLimit OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The upper limit for source of traffic stream(s)
        for which a QoS Policy rule is applied. Default
        value for this field is of all ones
        (255.255.255.255 for IPv4 and
        ffff:ffff:ffff:ffff:ffff:ffff:ffff:ffff: for IPv6),
        and it represents that no upper limit is specified for
        the Source IP address. Address format must be consistent
        with ocHnQosPolicyBoundaryAddressType."
    ::= { ocHnQosPolicyEntry 24 }

```

```

ocHnQosPolicyBoundarySourceAddressLowLimit OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The lower limit for source of traffic stream(s)
        for which a QoS Policy rule is applied. A default value for
        this field is all zeros (0.0.0.0 for IPv4 and :: for IPv6),
        which represents that no lower limit is specified. Address
        format must be consistent with
        ocHnQosPolicyBoundaryAddressType."
    ::= { ocHnQosPolicyEntry 25 }

ocHnQosPolicyBoundaryDestinationAddressUpLimit OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The upper limit for destination of traffic stream(s)
        for which a QoS Policy rule is applied. Default
        value for this field is of all ones
        (255.255.255.255 for IPv4 and
        ffff:ffff:ffff:ffff:ffff:ffff:ffff:ffff: for IPv6),
        and it represents that no upper limit is specified for
        the Destination IP address. Address format must be
        consistent with ocHnQosPolicyBoundaryAddressType."
    ::= { ocHnQosPolicyEntry 26 }

ocHnQosPolicyBoundaryDestinationAddressLowLimit OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The lower limit for destination of traffic stream(s)
        for which a QoS Policy rule is applied. A default value for
        this field is all zeros (0.0.0.0 for IPv4 and :: for IPv6),
        which represents that no lower limit is specified for the
        Destination IP address. Address format must be consistent
        with ocHnQosPolicyBoundaryAddressType."
    ::= { ocHnQosPolicyEntry 27 }

ocHnQosPolicyUserName OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This field identifies the name of the user initiating the
        UPnP-QoS action. The field is <= 64 UTF-8 characters.
        At present, the semantics for this field are not defined.
        A null should be returned if no value exists."
    ::= { ocHnQosPolicyEntry 28 }

ocHnQosPolicyVendorApplicationName OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This field identifies the name of the application
        initiating the UPnP-QoS Action. A NULL should be returned
        if no value exists."
    ::= { ocHnQosPolicyEntry 29 }

ocHnQosPolicyPortName OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-create
    STATUS      current

```

```

DESCRIPTION
    "This value, if present, contains a single URI string
    associated with the fixed port used by an application
    for its protocol set-up. A NULL should be returned if
    no value exists."
 ::= { ocHnQosPolicyEntry 30 }

ocHnQosPolicyServiceProviderServiceName OBJECT-TYPE
SYNTAX      SnmpAdminString
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "This object contains a single URI string associated with
    the name of the service offered by a service provider.
    A NULL should be returned if no value exists."
 ::= { ocHnQosPolicyEntry 31 }

ocHnQosPolicyCriticalFlag OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "Specifies the Critical Flag for traffic stream(s) for
    which a QoS Policy rule is applied. This flag can be set
    to get a higher UIN to protect a stream from preemption
    or to be able to always get admitted. Streams for
    entertainment are not critical traffic streams. This flag
    can be used for services like EAS messages, E-911 calls,
    voice calls, etc. The default value is False(2)."
 ::= { ocHnQosPolicyEntry 32 }

ocHnQosPolicyRequestedQosType OBJECT-TYPE
SYNTAX      INTEGER {
                fullyPrioritized(1),
                hybrid(2),
                fullyParameterized(3)
            }
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "Specifies the Requested QoS Type for traffic stream(s) for
    which a QoS Policy rule is applied. If supplied, it SHALL
    contain a non-negative integer value. It is used to
    indicate the type of Quality of Service that is requested
    for a traffic stream. The default value is 1."
 ::= { ocHnQosPolicyEntry 33 }

ocHnQosPolicyStartTime OBJECT-TYPE
SYNTAX      Unsigned32 (0..604800)
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "Specifies the starting Time Of Day (Day/Time)for a QoS
    Policy Rule. Time is specified in seconds and ranges
    from 0 - 604800 (to cover 7 days of week). Time 0 is Sunday
    12 midnight. If not specified, this object returns a NULL."
 ::= { ocHnQosPolicyEntry 34 }

ocHnQosPolicyEndTime OBJECT-TYPE
SYNTAX      Unsigned32 (0..604800)
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "Specifies the ending Time Of Day (Day/Time)for a QoS
    Policy Rule. Time is specified in seconds and ranges
    from 0 - 604800 (to cover 7 days of week). Time 0 is
    Sunday 12 midnight. If not specified, this object

```

```

        returns a NULL."
 ::= { ocHnQosPolicyEntry 35 }

ocHnQosPolicyTrafficLeaseTimeUpValue OBJECT-TYPE
    SYNTAX      Unsigned32 (0..604800)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the upper limit for lease time for reservation
        of QoS resources associated with traffic stream(s) for
        which a QoS Policy rule is applied. If not specified,
        this object returns a NULL."
 ::= { ocHnQosPolicyEntry 36 }

ocHnQosPolicyTrafficLeaseTimeLowValue OBJECT-TYPE
    SYNTAX      Unsigned32 (0..604800)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the lower limit for lease time for reservation
        of QoS resources associated with traffic stream(s) for
        which a QoS Policy rule is applied. If not specified, this
        object returns a NULL."
 ::= { ocHnQosPolicyEntry 37 }

ocHnQosPolicyRuleType OBJECT-TYPE
    SYNTAX      INTEGER {
        operatorOnly(0),
        homeUser(1),
        operatorForHomeUser(2),
        other(3)
        }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Identifies the type of a QoS Policy rule based
        on who configures the rule and for what purpose."
 ::= { ocHnQosPolicyEntry 38 }

ocHnQosPolicyRulePriority OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65535)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the priority for a QoS Policy rule. QoS policy
        rules are processed according to their Rule Priority value,
        the highest to the lowest."
 ::= { ocHnQosPolicyEntry 39 }

ocHnQosPolicyTrafficImportanceNumber OBJECT-TYPE
    SYNTAX      Unsigned32 (1..7)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies traffic priority to be utilized for tagging
        packets belonging to traffic stream(s) for which this
        QoS Policy Rule is applied."
 ::= { ocHnQosPolicyEntry 40 }

ocHnQosPolicyUserImportanceNumber OBJECT-TYPE
    SYNTAX      Unsigned32 (0..255)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies the User Importance Number for traffic stream(s)
        for which this QoS Policy Rule is applied. It determines
        the stream importance from users' perspective. It is used

```

```

        for admission control and preemption purposes."
 ::= { ocHnQosPolicyEntry 41 }

--
-- QoS Statistics for RSD Technologies only
--

ocHnQosROStatsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnQosROStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table reports the common values carried in each
        Rotameter Observation collected. It also provides the
        anchor index for the related tables (e.g., parameterized
        and prioritized stream statistics)."
 ::= { ocHnQos 3 }

ocHnQosROStatsEntry OBJECT-TYPE
    SYNTAX      OcHnQosROStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "One entry for each observation."
    INDEX { ocHnQosROStatsIndex }
 ::= { ocHnQosROStatsTable 1 }

OcHnQosROStatsEntry ::=
    SEQUENCE {
        ocHnQosROStatsIndex
            Unsigned32,
        ocHnQosROStatsIdentifier
            Unsigned32,
        ocHnQosROStatsMacAddress
            MacAddress,
        ocHnQosROStatsObservationMacAddress
            MacAddress,
        ocHnQosROStatsQosSegmentId
            OCTET STRING,
        ocHnQosROStatsTotalTrafficBytes
            Counter32,
        ocHnQosROStatsTotalParameterizedBytes
            Counter32,
        ocHnQosROStatsTotalParameterizedPackets
            Counter32,
        ocHnQosROStatsTotalParameterizedPacketsDropped
            Counter32,
        ocHnQosROStatsReportingDateAndTime
            SnmpAdminString,
        ocHnQosROStatsObservationPeriod
            Unsigned32,
        ocHnQosROStatsMonitorResolutionPeriod
            Unsigned32
    }

ocHnQosROStatsIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table Index. This will serve as an external index
        to related statistics tables."
 ::= { ocHnQosROStatsEntry 1 }

ocHnQosROStatsIdentifier OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only

```

```

STATUS      current
DESCRIPTION
    "Unique identifier for each observation on the device."
 ::= { ocHnQosROStatsEntry 2 }

ocHnQosROStatsMacAddress OBJECT-TYPE
SYNTAX      MacAddress
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "MAC Address of the interface on a device that is
    collecting these statistics."
 ::= { ocHnQosROStatsEntry 3 }

ocHnQosROStatsObservationMacAddress OBJECT-TYPE
SYNTAX      MacAddress
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "This is the MAC address of an interface on a QosDevice
    Service at which the Rotameter observation information
    is provided. If it is the same address as
    ocHnQosROStatsMacAddress parameter, then the Rotameter
    observation is for all traffic to/from the interface
    identified by the ocHnQosROStatsMacAddress field on this
    device. If the address is different from the
    OcHnQosROStatsMacAddress parameter, then the Rotameter
    observation is for all traffic between the interface
    identified by the ocHnQosROStatsObservationMacAddress field
    on another device (which may not be a QosDevice Service)
    and the interface identified by the
    ocHnQosROStatsMacAddress parameter on this device.
    If the address is all zeros, then the Rotameter observation
    is for the entire QosSegment of the shared media technology
    identified by the QosSegmentId. For example, this parameter
    will be set to all zeros by a device that is a Layer2
    scheduler for a QosSegment when reporting statistics
    information for the entire QosSegment."
 ::= { ocHnQosROStatsEntry 4 }

ocHnQosROStatsQosSegmentId OBJECT-TYPE
SYNTAX      OCTET STRING
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "This uniquely identifies a network segment of a shared
    Media technology. This parameter needs
    to be configured to obtain traffic statistics for a
    specific QosSegment and for a specific traffic stream
    identified by a combination of Layer2StreamId and a
    QosSegmentId. The default value of 0 indicates no
    QosSegment is specified."
 ::= { ocHnQosROStatsEntry 5 }

ocHnQosROStatsTotalTrafficBytes OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Total number of bytes of all streams (best effort,
    prioritized, and parameterized) measured in the
    observation period. A null value should be reported if
    no rotameter information is available."
 ::= { ocHnQosROStatsEntry 6 }

ocHnQosROStatsTotalParameterizedBytes OBJECT-TYPE
SYNTAX      Counter32

```

```

MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total number of bytes for all parameterized streams
    in the observation period. A null value should be
    reported if no rotameter information is available."
 ::= { ocHnQosROStatsEntry 7 }

ocHnQosROStatsTotalParameterizedPackets OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total number of packets of all parameterized
    streams measured in the observation period. A null value
    should be reported if no rotameter information is
    available."
 ::= { ocHnQosROStatsEntry 8 }

ocHnQosROStatsTotalParameterizedPacketsDropped OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total number of packets dropped at layer-2 for all the
    parameterized streams in the observation period. A null
    value should be reported if no rotameter information is
    available."
 ::= { ocHnQosROStatsEntry 9 }

ocHnQosROStatsReportingDateAndTime OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Time of Completion of Observation Period. This is wall
    clock time formatted per [RFC3339], which can potentially
    be non-synchronized with other devices on the network."
 ::= { ocHnQosROStatsEntry 10 }

ocHnQosROStatsObservationPeriod OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "This integer field specifies the duration in seconds over
    which the RotameterObservation is performed."
 ::= { ocHnQosROStatsEntry 11 }

ocHnQosROStatsMonitorResolutionPeriod OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "This integer field specifies, in seconds, how often a
    Rotameter observation is initiated."
 ::= { ocHnQosROStatsEntry 12 }

ocHnQosStreamStatisticsTable OBJECT-TYPE
SYNTAX SEQUENCE OF OcHnQosStreamStatisticsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "This table reports stream-specific statistics
    collected as a result of the current rotameter observation.
    Null values must be returned if no observations have been
    collected."

```

```

 ::= { ocHnQos 4 }

ocHnQosStreamStatisticsEntry OBJECT-TYPE
    SYNTAX      OcHnQosStreamStatisticsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "One entry report of counter values for
         each unique streamId."
    INDEX { ocHnQosROStatsIndex }
    ::= { ocHnQosStreamStatisticsTable 1 }

OcHnQosStreamStatisticsEntry ::=
    SEQUENCE {
        ocHnQosStreamStatisticsTrafficHandle
            OCTET STRING,
        ocHnQosStreamStatisticsLayer2StreamId
            OCTET STRING,
        ocHnQosStreamStatisticsPktsTransmitted
            Counter32,
        ocHnQosStreamStatisticsPktsReceived
            Counter32,
        ocHnQosStreamStatisticsErrorPktsDropped
            Counter32,
        ocHnQosStreamStatisticsBytesTransmitted
            Counter32,
        ocHnQosStreamStatisticsBytesReceived
            Counter32,
        ocHnQosStreamStatisticsPeakDataRateViolations
            TruthValue
    }

ocHnQosStreamStatisticsTrafficHandle OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Identifies a unique UPnP QoS traffic stream over the home
         network."
    ::= { ocHnQosStreamStatisticsEntry 1 }

ocHnQosStreamStatisticsLayer2StreamId OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (64) )
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Identifies a unique traffic stream over an RSD Technology
         Qos Segment identified by a QosSegmentId."
    ::= { ocHnQosStreamStatisticsEntry 2 }

ocHnQosStreamStatisticsPktsTransmitted OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This parameter reports total number of packets
         transmitted of a parameterized traffic stream
         specified in the current rotameter observation."
    ::= { ocHnQosStreamStatisticsEntry 3 }

ocHnQosStreamStatisticsPktsReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This parameter reports total number of packets
         received for a parameterized traffic stream specified

```

```

        in the current rotameter observation."
 ::= { ocHnQoSStreamStatisticsEntry 4 }

ocHnQoSStreamStatisticsErrorPktsDropped OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This parameter reports total number of dropped packets
         at layer-2 of a parameterized traffic stream specified in
         the current rotameter observation."
 ::= { ocHnQoSStreamStatisticsEntry 5 }

ocHnQoSStreamStatisticsBytesTransmitted OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This parameter reports total number of bytes transmitted of
         a parameterized traffic stream specified in
         the current rotameter observation."
 ::= { ocHnQoSStreamStatisticsEntry 6 }

ocHnQoSStreamStatisticsBytesReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This parameter reports total number of bytes
         received of the parameterized traffic stream
         specified in the current rotameter observation."
 ::= { ocHnQoSStreamStatisticsEntry 7 }

ocHnQoSStreamStatisticsPeakDataRateViolations OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "If true, this parameter indicates the source is exceeding
         specified peak data rate for a traffic stream over the
         Observation period."
 ::= { ocHnQoSStreamStatisticsEntry 8 }

--
-- QoS Priority-based Statistics for PSD devices only
--

ocHnQoSPriorityTrafficTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnQoSPriorityTrafficEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains a set of priority-based
         stream traffic statistics. It is indexed by the
         Rotameter Observation Statistics table index. This
         correlates each row in this table with each row
         (i.e., observation) in the ROSTatsTable."
 ::= { ocHnQoS 5 }

ocHnQoSPriorityTrafficEntry OBJECT-TYPE
    SYNTAX      OcHnQoSPriorityTrafficEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry reflects traffic statistics
         for one priority."
    INDEX { ocHnQoSROStatsIndex }

```

```

 ::= { ocHnQosPriorityTrafficTable 1 }

OcHnQosPriorityTrafficEntry ::=
SEQUENCE {
    ocHnQosTrafficTotalBytesPriority0
        Counter32,
    ocHnQosTrafficTotalBytesPriority1
        Counter32,
    ocHnQosTrafficTotalBytesPriority2
        Counter32,
    ocHnQosTrafficTotalBytesPriority3
        Counter32,
    ocHnQosTrafficTotalBytesPriority4
        Counter32,
    ocHnQosTrafficTotalBytesPriority5
        Counter32,
    ocHnQosTrafficTotalBytesPriority6
        Counter32,
    ocHnQosTrafficTotalBytesPriority7
        Counter32
}

ocHnQosTrafficTotalBytesPriority0 OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total number of bytes of all strictly prioritized
    flows interpreted as TrafficImportanceNumber '0'
    during the Observation period."
 ::= { ocHnQosPriorityTrafficEntry 1 }

ocHnQosTrafficTotalBytesPriority1 OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total number of bytes of all strictly prioritized
    flows interpreted as TrafficImportanceNumber '1'
    during the Observation period."
 ::= { ocHnQosPriorityTrafficEntry 2 }

ocHnQosTrafficTotalBytesPriority2 OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total number of bytes of all strictly prioritized
    flows interpreted as TrafficImportanceNumber '2'
    during the Observation period."
 ::= { ocHnQosPriorityTrafficEntry 3 }

ocHnQosTrafficTotalBytesPriority3 OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Total number of bytes of all strictly prioritized
    flows interpreted as TrafficImportanceNumber '3'
    during the Observation period."
 ::= { ocHnQosPriorityTrafficEntry 4 }

ocHnQosTrafficTotalBytesPriority4 OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION

```

```

        "Total number of bytes of all strictly prioritized
        flows interpreted as TrafficImportanceNumber '4'
        during the Observation period."
 ::= { ocHnQosPriorityTrafficEntry 5 }

ocHnQosTrafficTotalBytesPriority5 OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of bytes of all strictly prioritized
        flows interpreted as TrafficImportanceNumber '5'
        during the Observation period."
 ::= { ocHnQosPriorityTrafficEntry 6 }

ocHnQosTrafficTotalBytesPriority6 OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of bytes of all strictly prioritized
        flows interpreted as TrafficImportanceNumber '6'
        during the Observation period."
 ::= { ocHnQosPriorityTrafficEntry 7 }

ocHnQosTrafficTotalBytesPriority7 OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total number of bytes of all strictly prioritized
        flows interpreted as TrafficImportanceNumber '7'
        during the Observation period."
 ::= { ocHnQosPriorityTrafficEntry 8 }

--
-- Device addressing and operational status information
--

ocHnDevInterfaceStatus OBJECT IDENTIFIER ::= { ocHnMibObjects 4 }

ocHnDevInterfaceConfigTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnDevInterfaceConfigEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table augments the ifTable for each HN interface.
        It provides the mechanism for modifying and displaying
        interface characteristics not addressed by the IETF
        ifTable. The index values will serve as an external index
        to the ocHnDevStatus tables."
 ::= { ocHnDevInterfaceStatus 1 }

ocHnDevInterfaceConfigEntry OBJECT-TYPE
    SYNTAX      OcHnDevInterfaceConfigEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry describes an interface for a specific
        technology."
    INDEX { ifIndex }
 ::= { ocHnDevInterfaceConfigTable 1 }

OcHnDevInterfaceConfigEntry ::=
    SEQUENCE {
        ocHnDevInterfaceConfigMaxPowerLevel
            Integer32,

```

```

    ocHnDevInterfaceConfigPowerUnits
        PowerUnit,
    ocHnDevInterfaceConfigMaxParameterizedBandwidth
        Unsigned32,
    ocHnDevInterfaceConfigEnableEncryption
        INTEGER,
    ocHnDevInterfaceConfigEncryptionPassphrase
        SnmpAdminString
    }

ocHnDevInterfaceConfigMaxPowerLevel OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Maximum power level used by an RSD Technology node.
        This level is combined with the measurement units
        defined in ocHnDevInterfaceConfigPowerUnits."
    ::= { ocHnDevInterfaceConfigEntry 2 }

ocHnDevInterfaceConfigPowerUnits OBJECT-TYPE
    SYNTAX      PowerUnit
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Reports the power units of measurement/reporting
        in ocHnDevInterfacePowerUnits used by the RSD
        technology on the interface being
        reported."
    ::= { ocHnDevInterfaceConfigEntry 3 }

ocHnDevInterfaceConfigMaxParameterizedBandwidth OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This object requests the maximum bandwidth, as a
        percentage of total bandwidth, to be made available for
        parameterized traffic streams. The actual bandwidth made
        available for parameterized streams is represented by
        ocHnDevInterfaceStatusMaxParameterizedBandwidth object.
        This configuration takes effect only if the node
        is the Layer2Scheduler for the RSD Technology interface
        (i.e., if the ocHnDevInterfaceStatusLayer2Scheduler object
        is set to true on this node)."
    ::= { ocHnDevInterfaceConfigEntry 4 }

ocHnDevInterfaceConfigEnableEncryption OBJECT-TYPE
    SYNTAX      INTEGER
                {
                    enabled(1),
                    disabled(2)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "A Boolean parameter used to enable or disable privacy
        (link layer encryption) on the RSD Technology. The default
        is disabled(2)."
    ::= { ocHnDevInterfaceConfigEntry 5 }

ocHnDevInterfaceConfigEncryptionPassphrase OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE (24 | 32) )
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "A Password or a key used for encrypting data sent over

```

```

        the RSD Technology using technology-specific encryption
        algorithm."
 ::= { ocHnDevInterfaceConfigEntry 6 }

--
-- Device Network Operating Status
--

ocHnDevInterfaceStatusTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnDevInterfaceStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table tracks and reports current network
        related attributes for each interface (e.g., MAC)."
 ::= { ocHnDevInterfaceStatus 2 }

ocHnDevInterfaceStatusEntry OBJECT-TYPE
    SYNTAX      OcHnDevInterfaceStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry associates the network operational
        assignments for each interface."
    INDEX { ifIndex }
 ::= { ocHnDevInterfaceStatusTable 1 }

OcHnDevInterfaceStatusEntry ::=
    SEQUENCE {
        ocHnDevInterfaceStatusTxBroadcastRate
            Unsigned32,
        ocHnDevInterfaceStatusTxBroadcastLevel
            Tenths,
        ocHnDevInterfaceStatusMaxTxPowerLevel
            Tenths,
        ocHnDevInterfaceStatusPowerUnits
            PowerUnit,
        ocHnDevInterfaceStatusMaxParameterizedBandwidth
            Unsigned32,
        ocHnDevInterfaceStatusLayer2Scheduler
            TruthValue
    }

ocHnDevInterfaceStatusTxBroadcastRate OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "bits/sec"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Broadcast transmit rate (bits/sec) for this interface."
 ::= { ocHnDevInterfaceStatusEntry 1 }

ocHnDevInterfaceStatusTxBroadcastLevel OBJECT-TYPE
    SYNTAX      Tenths
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The power level used for transmission of broadcast
        messages by the RSD node reported in units defined by
        ocHnDevInterfaceStatusPowerUnits."
 ::= { ocHnDevInterfaceStatusEntry 2 }

ocHnDevInterfaceStatusMaxTxPowerLevel OBJECT-TYPE
    SYNTAX      Tenths
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION

```

```

        "The absolute maximum power level that a node
        is capable of transmitting. The power units
        are defined in ocHnDevInterfaceStatusPowerUnits."
 ::= { ocHnDevInterfaceStatusEntry 3 }

ocHnDevInterfaceStatusPowerUnits OBJECT-TYPE
    SYNTAX      PowerUnit
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Reports the power units of measurement/reporting
        in ocHnDevInterfacePowerUnits used by the RSD
        technology on the interface being reported."
 ::= { ocHnDevInterfaceStatusEntry 4 }

ocHnDevInterfaceStatusMaxParameterizedBandwidth OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The actual bandwidth, as a percentage of total, that can
        be utilized for reservation-based (parameterized)
        traffic streams. A value of '0' should be reported if
        this node is not a layer2scheduler for the RSD Technology
        interface (i.e., if the
        ocHnDevInterfaceStatusLayer2Scheduler
        object is set to false on this node)."
 ::= { ocHnDevInterfaceStatusEntry 5 }

ocHnDevInterfaceStatusLayer2Scheduler OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This Boolean parameter indicates whether this particular
        node is a layer-2 scheduler."
 ::= { ocHnDevInterfaceStatusEntry 6 }

--
-- Logical Device Connection Table
--

ocHnDevConnectionTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF OcHnDevConnectionEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table defines the logical connections, by MAC,
        of all the devices known to this interface."
 ::= { ocHnDevInterfaceStatus 3 }

ocHnDevConnectionEntry OBJECT-TYPE
    SYNTAX      OcHnDevConnectionEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry associates the network operational
        attributes of the connections for each interface."
    INDEX { ifIndex, ocHnDevConnectionIndex }
 ::= { ocHnDevConnectionTable 1 }

OcHnDevConnectionEntry ::=
    SEQUENCE {
        ocHnDevConnectionIndex
            Unsigned32,
        ocHnDevConnectionDestMac
            MacAddress,

```

```

    ocHnDevConnectionRxLinkRate
        Unsigned32,
    ocHnDevConnectionRxModulationType
        SnmpAdminString,
    ocHnDevConnectionRxBroadcastRate
        Unsigned32,
    ocHnDevConnectionRxSignalStrength
        Tenths,
    ocHnDevConnectionTxUnicastLevel
        Tenths,
    ocHnDevConnectionPowerUnits
        PowerUnit,
    ocHnDevConnectionTxLinkRate
        Unsigned32,
    ocHnDevConnectionTxModulationType
        SnmpAdminString
    }

ocHnDevConnectionIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Secondary index of the connection table."
    ::= { ocHnDevConnectionEntry 1 }

ocHnDevConnectionDestMac OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "MAC of other device if visible to
        this device."
    ::= { ocHnDevConnectionEntry 2 }

ocHnDevConnectionRxLinkRate OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "bits/sec"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "PHY reception rate (bits/sec) on this interface
        from the node identified by its MAC address."
    ::= { ocHnDevConnectionEntry 3 }

ocHnDevConnectionRxModulationType OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Type of modulation currently being used by an
        interface on this node for reception from the
        node identified by MAC address. A value is required
        only if this is an RF technology-based connection.
        Non-RF interfaces should report 'n/a'."
    ::= { ocHnDevConnectionEntry 4 }

ocHnDevConnectionRxBroadcastRate OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "bits/sec"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Receive rate (bits/sec) at this RSD Interface for
        broadcasts initiated by the logically connected node
        identified by the destination MAC Address in

```

```

        this table entry."
 ::= { ocHnDevConnectionEntry 5 }

ocHnDevConnectionRxSignalStrength OBJECT-TYPE
    SYNTAX      Tenths
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The signal strength received at this
        interface from the associated node identified by
        the MAC address. The power units are defined
        in ocHnDevConnectionPowerUnits "
 ::= { ocHnDevConnectionEntry 6 }

ocHnDevConnectionTxUnicastLevel OBJECT-TYPE
    SYNTAX      Tenths
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The power level used for transmission of unicast
        messages by the RSD node reported in units
        defined in ocHnDevConnectionPowerUnits for
        this interface."
 ::= { ocHnDevConnectionEntry 7 }

ocHnDevConnectionPowerUnits OBJECT-TYPE
    SYNTAX      PowerUnit
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Reports the power units of measurement/reporting
        in ocHnDevInterfacePowerUnits used by the RSD
        technology on the interface being
        reported."
 ::= { ocHnDevConnectionEntry 8 }

ocHnDevConnectionTxLinkRate OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "bits/sec"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "PHY transmission rate (bits/sec) from this interface
        to the node identified by MAC addresses."
 ::= { ocHnDevConnectionEntry 9 }

ocHnDevConnectionTxModulationType OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The modulation type currently employed by this
        interface while transmitting to the node
        identified by its MAC address. A value is required
        only if this is an RF technology-based connection.
        Non-RF interfaces should report 'n/a'."
 ::= { ocHnDevConnectionEntry 10 }

--

ocHnConformance      OBJECT IDENTIFIER ::= { ocHnMibModule 3 }
ocHnMIBCompliances   OBJECT IDENTIFIER ::= { ocHnConformance 1 }
ocHnMIBGroups        OBJECT IDENTIFIER ::= { ocHnConformance 2 }

-- Compliance statements

ocHnMIBCompliance   MODULE-COMPLIANCE

```

```

STATUS      current
DESCRIPTION
    "The requirements for conformance to the OpenCable
    Home Networking MIB."
MODULE -- this module
MANDATORY-GROUPS {
    ocHnHomeNetworkStatusGroup,
    ocHnGenericDevInterfaceGroup
}

GROUP ocHnRotameterConfigGroup
DESCRIPTION
    "This group is an optional implementation."

GROUP ocHnQosTrafficDescInfo
DESCRIPTION
    "This group is an optional implementation."

GROUP ocHnQosGroup
DESCRIPTION
    "This group is an optional implementation."
 ::= { ocHnMIBCompliances 1 }

ocHnHomeNetworkStatusGroup OBJECT-GROUP
OBJECTS {
    ocHnRsdManagerImportanceNumber,
    ocHnRsdManagerPreferredStatus,
    ocHnDevUpnpServiceType,
    ocHnDevUpnpServiceAvailable,
    ocHnDevSupportedChannelLastOperatingFreq,
    ocHnDevSupportedChannelInUse,
    ocHnDevSupportedChannelFrequency,
    ocHnDevSupportedChannelEligible,
    ocHnDevPropertiesFriendlyName
}
STATUS      current
DESCRIPTION
    "Defines the objects used to report the status
    of the home network."
 ::= { ocHnMIBGroups 1 }

ocHnGenericDevInterfaceGroup OBJECT-GROUP
OBJECTS {
    ocHnDevInterfaceConfigMaxPowerLevel,
    ocHnDevInterfaceConfigPowerUnits,
    ocHnDevInterfaceConfigMaxParameterizedBandwidth,
    ocHnDevInterfaceConfigEnableEncryption,
    ocHnDevInterfaceConfigEncryptionPassphrase,
    ocHnDevInterfaceStatusLayer2Scheduler,
    ocHnDevInterfaceStatusTxBroadcastLevel,
    ocHnDevInterfaceStatusTxBroadcastRate,
    ocHnDevInterfaceStatusMaxTxPowerLevel,
    ocHnDevInterfaceStatusPowerUnits,
    ocHnDevInterfaceStatusMaxParameterizedBandwidth,
    ocHnDevConnectionDestMac,
    ocHnDevConnectionRxLinkRate,
    ocHnDevConnectionRxModulationType,
    ocHnDevConnectionRxBroadcastRate,
    ocHnDevConnectionRxSignalStrength,
    ocHnDevConnectionPowerUnits,
    ocHnDevConnectionTxUnicastLevel,
    ocHnDevConnectionTxLinkRate,
    ocHnDevConnectionTxModulationType
}
STATUS      current
DESCRIPTION
    "The objects common to all the OCHN interfaces."

```

```

 ::= { ocHnMIBGroups 2 }

ocHnRotameterConfigGroup OBJECT-GROUP
OBJECTS
    {
        ocHnRotameterConfigRowStatus,
        ocHnRotameterConfigQosSegmentId,
        ocHnRotameterConfigObservationActive,
        ocHnRotameterConfigEndpointMacAddress,
        ocHnRotameterConfigPeriod,
        ocHnRotameterConfigMonitorResolutionPeriod,
        ocHnPerStreamRotameterConfigRowStatus,
        ocHnPerStreamRotameterConfigLayer2StreamId,
        ocHnPerStreamRotameterConfigTrafficHandle,
        ocHnPerStreamRotameterConfigObservationActive
    }
STATUS
    current
DESCRIPTION
    "The collection of objects used to create one or more
    Rotameter configurations that may be activated via
    SNMP."
 ::= { ocHnMIBGroups 3 }

ocHnQosTrafficDescInfo OBJECT-GROUP
OBJECTS
    {
        ocHnQosStreamsInfoCollectionTrigger,
        ocHnQosTrafficQDMacAddress,
        ocHnQosTrafficHandle,
        ocHnQosTrafficNetworkAddressType,
        ocHnQosTrafficSourceAddress,
        ocHnQosTrafficSourcePort,
        ocHnQosTrafficDestinationAddress,
        ocHnQosTrafficDestinationPort,
        ocHnQosTrafficIpProtocol,
        ocHnQosTrafficV3TrafficIdSourceUuid,
        ocHnQosTrafficV3TrafficIdDestinationUuid,
        ocHnQosTrafficMediaServerConnectionId,
        ocHnQosTrafficMediaRendererConnectionId,
        ocHnQosTrafficLeaseTime,
        ocHnQosTrafficCritical,
        ocHnQosTrafficUserName,
        ocHnQosTrafficVendorApplicationName,
        ocHnQosTrafficPortName,
        ocHnQosTrafficServiceProviderServiceName,
        ocHnQosTrafficCpName,
        ocHnQosTspec,
        ocHnQosActiveTspec,
        ocHnQosTspecTrafficClass,
        ocHnQosTspecReqQosType,
        ocHnQosTspecDataRate,
        ocHnQosTspecPeakDataRate,
        ocHnQosTspecMaxBurstSize,
        ocHnQosTspecMaxPacketSize,
        ocHnQosTspecE2EMaxDelayHigh,
        ocHnQosTspecE2EMaxJitter,
        ocHnQosPolicyRowStatus,
        ocHnQosPolicyIpAddressType,
        ocHnQosPolicySourceAddressUpLimit,
        ocHnQosPolicySourceAddressLowLimit,
        ocHnQosPolicySourcePortUpLimit,
        ocHnQosPolicySourcePortLowLimit,
        ocHnQosPolicyDestinationAddressUpLimit,
        ocHnQosPolicyDestinationAddressLowLimit,
        ocHnQosPolicyDestinationPortUpLimit,
        ocHnQosPolicyDestinationPortLowLimit,
        ocHnQosPolicyIpProtocolUpLimit,
        ocHnQosPolicyIpProtocolLowLimit,
    }

```

```

        ocHnQosPolicyTrafficClass,
        ocHnQosPolicyPeakDataRateUpLimit,
        ocHnQosPolicyPeakDataRateLowLimit,
        ocHnQosPolicyMeanDataRateUpLimit,
        ocHnQosPolicyMeanDataRateLowLimit,
        ocHnQosPolicyMaxBurstSizeUpLimit,
        ocHnQosPolicyMaxBurstSizeLowLimit,
        ocHnQosPolicyE2EMaxDelayHighLimit,
        ocHnQosPolicyE2EMaxDelayLowLimit,
        ocHnQosPolicyBoundaryAddressType,
        ocHnQosPolicyBoundarySourceAddressUpLimit,
        ocHnQosPolicyBoundarySourceAddressLowLimit,
        ocHnQosPolicyBoundaryDestinationAddressUpLimit,
        ocHnQosPolicyBoundaryDestinationAddressLowLimit,
        ocHnQosPolicyUserName,
        ocHnQosPolicyVendorApplicationName,
        ocHnQosPolicyPortName,
        ocHnQosPolicyServiceProviderServiceName,
        ocHnQosPolicyCriticalFlag,
        ocHnQosPolicyRequestedQosType,
        ocHnQosPolicyStartTime,
        ocHnQosPolicyEndTime,
        ocHnQosPolicyTrafficLeaseTimeUpValue,
        ocHnQosPolicyTrafficLeaseTimeLowValue,
        ocHnQosPolicyRuleType,
        ocHnQosPolicyRulePriority,
        ocHnQosPolicyTrafficImportanceNumber,
        ocHnQosPolicyUserImportanceNumber
    }
STATUS      current
DESCRIPTION
    "List of objects used to acquire QOS traffic attributes
    as well as set QOS Policies."
 ::= { ocHnMIBGroups 4 }

ocHnQosGroup OBJECT-GROUP
OBJECTS     {
    ocHnQosROStatsIdentifier,
    ocHnQosROStatsMacAddress,
    ocHnQosROStatsObservationMacAddress,
    ocHnQosROStatsQosSegmentId,
    ocHnQosROStatsTotalTrafficBytes,
    ocHnQosROStatsTotalParameterizedBytes,
    ocHnQosROStatsTotalParameterizedPackets,
    ocHnQosROStatsTotalParameterizedPacketsDropped,
    ocHnQosROStatsReportingDateAndTime,
    ocHnQosROStatsObservationPeriod,
    ocHnQosROStatsMonitorResolutionPeriod,
    ocHnQosStreamStatisticsLayer2StreamId,
    ocHnQosStreamStatisticsPktsTransmitted,
    ocHnQosStreamStatisticsPktsReceived,
    ocHnQosStreamStatisticsErrorPktsDropped,
    ocHnQosStreamStatisticsBytesTransmitted,
    ocHnQosStreamStatisticsBytesReceived,
    ocHnQosStreamStatisticsTrafficHandle,
    ocHnQosStreamStatisticsPeakDataRateViolations,
    ocHnQosTrafficTotalBytesPriority0,
    ocHnQosTrafficTotalBytesPriority1,
    ocHnQosTrafficTotalBytesPriority2,
    ocHnQosTrafficTotalBytesPriority3,
    ocHnQosTrafficTotalBytesPriority4,
    ocHnQosTrafficTotalBytesPriority5,
    ocHnQosTrafficTotalBytesPriority6,
    ocHnQosTrafficTotalBytesPriority7
}
STATUS      current
DESCRIPTION

```

```
        "Parameterized and prioritized traffic flow objects."  
 ::= { ocHnMIBGroups 5 }  
END
```

Annex A MIB Object Requirements

This annex defines the SNMP MIB modules and MIB variables required for the Open Cable Home Network Extension.

Table A-1 - MIB Implementation Support

Requirement Type	Table Notation	Description
Conditional Mandatory	C	The object MUST be implemented if and only if an optional underlying technology is implemented and is not represented by an external MIB.
Deprecated	D	Deprecated objects are optional. If a vendor chooses to implement the object, the object MUST be implemented correctly according to the MIB definition. If a vendor chooses not to implement the object, an agent MUST NOT instantiate such object and MUST respond with the appropriate error/exception condition (e.g., no such object for SNMPv2c).
Mandatory	M	The object MUST be implemented correctly according to the MIB definition.
Not Applicable	NA	Not applicable to the device.
Not Supported	N-SUP	An agent MUST NOT instantiate such object and MUST respond with the appropriate error/exception condition (e.g., no such object for SNMPv2c).
Optional	O	A vendor can choose to implement or not implement the object. If a vendor chooses to implement the object, the object MUST be implemented correctly according to the MIB definition. If a vendor chooses not to implement the object, an agent MUST NOT instantiate such object and MUST respond with the appropriate error/exception condition (e.g., no such object for SNMPv2c).
Obsolete	Ob	In SNMP convention, obsolete objects should not be implemented. This specification allows vendors to implement or not implement obsolete objects. If a vendor chooses to implement an obsoleted object, the object MUST be implemented correctly according to the MIB definition. If a vendor chooses not to implement the obsoleted object, the SNMP agent MUST NOT instantiate such object and MUST respond with the appropriate error/exception condition (e.g., 'noSuchObject' for SNMPv2c).

Table A-2 - SNMP Access Requirements

SNMP Access Type	Table Notation	Description
Not Accessible	N-ACC	The object is not accessible and is usually an index in a table.
RC	Read Create	The access of the object MUST be implemented as Read-Create.
RW	Read Write	The access of the object MUST be implemented as Read-Only.
RO	Read Only	The access of the object MUST be implemented as Read-Write.
RC/RO	Read Create or Read Only	The access of the object MUST be implemented as either Read-Create or Read-Only as described in the MIB definition.
RW/RO	Read Write / Read Only	The access of the object MUST be implemented as either Read-Write or Read-Only as described in the MIB definition.
Accessible for SNMP Notifications	ACC-FN	These objects are used for SNMP Notifications by the CMTS and CM SNMP Agents.

MIB Objects		
OC-HOME-NETWORK-MIB		
ocHnRsdManagerStatus		
Object	Req	Access
ocHnRsdManagerImportanceNumber	M	RW
ocHnRsdManagerPreferredStatus	M	RO
ocHnDevUpnpServiceTable		
Object	Req	Access
ocHnDevUpnpServiceIndex	M	N-Acc
ocHnDevUpnpServiceType	M	RO
ocHnDevUpnpServiceAvailable	M	RO
ocHnDevSupportedChannelTable		
Object	Req	Access
ocHnDevSupportedChannelIndex	C	RO
ocHnDevSupportedChannelLastOperatingFreq	C	RO
ocHnDevSupportedChannelInUse	C	RW
ocHnDevSupportedChannelFrequency	C	RO
ocHnDevSupportedChannelEligible	C	RW
ocHnDevProperties		
Object	Req	Access
ocHnDevPropertiesFriendlyName	M	RO
ocHnRotameterConfigTable		
Object	Req	Access
ocHnRotameterConfigIndex	O	N-Acc
ocHnRotameterConfigRowStatus	O	RC
ocHnRotameterConfigObservationActive	O	RC
ocHnRotameterConfigPeriod	O	RC
ocHnRotameterConfigMonitorResolutionPeriod	O	RC
ocHnRotameterConfigQosSegmentId	O	RC
ocHnRotameterConfigEndpointMacAddress	O	RC
ocHnPerStreamRotameterConfigTable		
Object	Req	Access
ocHnPerStreamRotameterConfigIndex	O	N-Acc
ocHnPerStreamRotameterConfigRowStatus	O	RC
ocHnPerStreamRotameterConfigLayer2StreamId	O	RC
ocHnPerStreamRotameterConfigTrafficHandle	O	RC
ocHnPerStreamRotameterConfigObservationActive	O	RC
ocHnQosTrafficInfo		
Object	Req	Access
ocHnQosStreamsInfoCollectionTrigger	O	RW
ocHnQosTrafficDescTable		
Object	Req	Access
ocHnQosTrafficDescIndex	O	N-Acc
ocHnQosTrafficHandle	O	RO
ocHnQosTrafficQDMacAddress	O	RO
ocHnQosTrafficNetworkAddressType	O	RO

MIB Objects		
ocHnQosTrafficSourceAddress	0	RO
ocHnQosTrafficSourcePort	0	RO
ocHnQosTrafficDestinationAddress	0	RO
ocHnQosTrafficDestinationPort	0	RO
ocHnQosTrafficIppProtocol	0	RO
ocHnQosTrafficV3TrafficIdSourceUid	0	RO
ocHnQosTrafficV3TrafficIdDestinationUid	0	RO
ocHnQosTrafficMediaServerConnectionId	0	RO
ocHnQosTrafficMediaRendererConnectionId	0	RO
ocHnQosTrafficLeaseTime	0	RO
ocHnQosTrafficCritical	0	RO
ocHnQosTrafficUserName	0	RO
ocHnQosTrafficVendorApplicationName	0	RO
ocHnQosTrafficPortName	0	RO
ocHnQosTrafficServiceProviderServiceName	0	RO
ocHnQosTrafficCpName	0	RO
ocHnQosTspecTable		
Object	Req	Access
ocHnQosTspecTableIndex	0	N-Acc
ocHnQosTspec	0	RO
ocHnQosActiveTspec	0	RO
ocHnQosTspecTrafficClass	0	RO
ocHnQosTspecReqQosType	0	RO
ocHnQosTspecDataRate	0	RO
ocHnQosTspecPeakDataRate	0	RO
ocHnQosTspecMaxBurstSize	0	RO
ocHnQosTspecMaxPacketSize	0	RO
ocHnQosTspecE2EMaxDelayHigh	0	RO
ocHnQosTspecE2EMaxJitter	0	RO
ocHnQosPolicyTable		
Object	Req	Access
ocHnQosPolicyRuleIdentifier	0	N-Acc
ocHnQosPolicyRowStatus	0	RC
ocHnQosPolicyIpAddressType	0	RC
ocHnQosPolicySourceAddressUpLimit	0	RC
ocHnQosPolicySourceAddressLowLimit	0	RC
ocHnQosPolicySourcePortUpLimit	0	RC
ocHnQosPolicySourcePortLowLimit	0	RC
ocHnQosPolicyDestinationAddressUpLimit	0	RC
ocHnQosPolicyDestinationAddressLowLimit	0	RC
ocHnQosPolicyDestinationPortUpLimit	0	RC
ocHnQosPolicyDestinationPortLowLimit	0	RC
ocHnQosPolicyIppProtocolUpLimit	0	RC
ocHnQosPolicyIppProtocolLowLimit	0	RC
ocHnQosPolicyTrafficClass	0	RC
ocHnQosPolicyPeakDataRateUpLimit	0	RC
ocHnQosPolicyPeakDataRateLowLimit	0	RC
ocHnQosPolicyMeanDataRateUpLimit	0	RC
ocHnQosPolicyMeanDataRateLowLimit	0	RC
ocHnQosPolicyMaxBurstSizeUpLimit	0	RC
ocHnQosPolicyMaxBurstSizeLowLimit	0	RC

MIB Objects		
ocHnQosPolicyE2EMaxDelayHighLimit	0	RC
ocHnQosPolicyE2EMaxDelayLowLimit	0	RC
ocHnQosPolicyBoundaryAddressType	0	RC
ocHnQosPolicyBoundarySourceAddressUpLimit	0	RC
ocHnQosPolicyBoundarySourceAddressLowLimit	0	RC
ocHnQosPolicyBoundaryDestinationAddressUpLimit	0	RC
ocHnQosPolicyBoundaryDestinationAddressLowLimit	0	RC
ocHnQosPolicyUserName	0	RC
ocHnQosPolicyVendorApplicationName	0	RC
ocHnQosPolicyPortName	0	RC
ocHnQosPolicyServiceProviderServiceName	0	RC
ocHnQosPolicyCriticalFlag	0	RC
ocHnQosPolicyRequestedQosType	0	RC
ocHnQosPolicyStartTime	0	RC
ocHnQosPolicyEndTime	0	RC
ocHnQosPolicyTrafficLeaseTimeUpValue	0	RC
ocHnQosPolicyTrafficLeaseTimeLowValue	0	RC
ocHnQosPolicyRuleType	0	RC
ocHnQosPolicyRulePriority	0	RC
ocHnQosPolicyTrafficImportanceNumber	0	RC
ocHnQosPolicyUserImportanceNumber	0	RC
ocHnQosROStatsTable		
Object	Req	Access
ocHnQosROStatsIndex	0	N-Acc
ocHnQosROStatsIdentifier	0	RO
ocHnQosROStatsMacAddress	0	RO
ocHnQosROStatsObservationMacAddress	0	RO
ocHnQosROStatsQosSegmentId	0	RO
ocHnQosROStatsTotalTrafficBytes	0	RO
ocHnQosROStatsTotalParameterizedBytes	0	RO
ocHnQosROStatsTotalParameterizedPackets	0	RO
ocHnQosROStatsTotalParameterizedPacketsDropped	0	RO
ocHnQosROStatsReportingDateAndTime	0	RO
ocHnQosROStatsObservationPeriod	0	RO
ocHnQosROStatsMonitorResolutionPeriod	0	RO
ocHnQosStreamStatisticsTable		
Object	Req	Access
ocHnQosStreamStatisticsTrafficHandle	0	RO
ocHnQosStreamStatisticsLayer2StreamId	0	RO
ocHnQosStreamStatisticsPktsTransmitted	0	RO
ocHnQosStreamStatisticsPktsReceived	0	RO
ocHnQosStreamStatisticsErrorPktsDropped	0	RO
ocHnQosStreamStatisticsBytesTransmitted	0	RO
ocHnQosStreamStatisticsBytesReceived	0	RO
ocHnQosStreamStatisticsPeakDataRateViolations	0	RO
ocHnQosPriorityTrafficTable (PSD only)		
Object	Req	Access
ocHnQosTrafficTotalBytesPriority0	0	RO
ocHnQosTrafficTotalBytesPriority1	0	RO

MIB Objects		
ocHnQosTrafficTotalBytesPriority2	O	RO
ocHnQosTrafficTotalBytesPriority3	O	RO
ocHnQosTrafficTotalBytesPriority4	O	RO
ocHnQosTrafficTotalBytesPriority5	O	RO
ocHnQosTrafficTotalBytesPriority6	O	RO
ocHnQosTrafficTotalBytesPriority7	O	RO
ocHnDevInterfaceConfigTable		
Object	Req	Access
ocHnDevInterfaceConfigMaxPowerLevel	M	RW
ocHnDevInterfaceConfigPowerUnits	M	RO
ocHnDevInterfaceConfigMaxParameterizedBandwidth	M	RW
ocHnDevInterfaceConfigEnableEncryption	M	RW
ocHnDevInterfaceConfigEncryptionPassphrase	M	RW
ocHnDevInterfaceStatusTable		
Object	Req	Access
ocHnDevInterfaceStatusTxBroadcastRate	M	RO
ocHnDevInterfaceStatusTxBroadcastLevel	M	RO
ocHnDevInterfaceStatusMaxTxPowerLevel	M	RO
ocHnDevInterfaceStatusPowerUnits	M	RO
ocHnDevInterfaceStatusMaxParameterizedBandwidth	M	RO
ocHnDevInterfaceStatusLayer2Scheduler	M	RO
ocHnDevConnectionTable		
Object	Req	Access
ocHnDevConnectionIndex	M	N-Acc
ocHnDevConnectionDestMac	M	RO
ocHnDevConnectionRxLinkRate	M	RO
ocHnDevConnectionRxModulationType	M	RO
ocHnDevConnectionRxBroadcastRate	M	RO
ocHnDevConnectionRxSignalStrength	M	RO
ocHnDevConnectionTxUnicastLevel	M	RO
ocHnDevConnectionPowerUnits	M	RO
ocHnDevConnectionTxLinkRate	M	RO
ocHnDevConnectionTxModulationType	M	RO
IF-MIB (RFC2863)		
ifTable		
Object	Req	Access
ifIndex	M	RO
ifDescr	M	RO
ifType	M	RO
ifMtu	M	RO
ifSpeed	M	RO
ifPhysAddress	M	RO
ifAdminStatus	M	RW
ifOperStatus	M	RO
ifLastChange	M	RO
ifInOctets	M	RO
ifInUcastPkts	M	RO
ifInDiscards	M	RO

MIB Objects		
ifInErrors	M	RO
ifInUnknownProtos	M	RO
ifOutOctets	M	RO
ifOutUcastPkts	M	RO
ifOutDiscards	M	RO
ifOutErrors	M	RO
ifXTable		
Object	Req	Access
ifName	M	RO
ifInMulticastPkts	M	RO
ifInBroadcastPkts	M	RO
ifOutMulticastPkts	M	RO
ifOutBroadcastPkts	M	RO

Appendix I OCHN MIB Maps

The information in the following tables provides an informational resource for those who may be interested in contrasting the required OCHN MIB with implemented RSD technology-specific MIBs. For example, network operators might find the information helpful to distinguish the differences between similar MIB objects.

I.1 OCHN to MoCA MIB Map

OCAP HN MIB Object-Type	MoCA11 MIB v1.01 Object-Type	Comments/Notes:
Reserved Services Domain Status Objects		
ocHnRsdManagerImportanceNumber	N/A	
ocHnRsdManagerPreferredStatus	N/A	
UPnP Services Status information Objects		
ocHnDevUpnpServiceType	N/A	
ocHnDevUpnpServiceAvailable	N/A	
Supported Channels Table Objects		
ocHnDevSupportedChannelLastOperatingFreq	mocalfLOF	
ocHnDevSupportedChannelInUse	mocalfRFChannel	
ocHnDevSupportedChannelFrequency	mocalfChannelMask	
ocHnDevSupportedChannelEligible	mocalfChannelMask	
Rotameter configuration options objects		
ocHnRotameterConfigRowStatus	N/A	
ocHnRotameterConfigObservationActive	N/A	
ocHnRotameterConfigPeriod	N/A	
ocHnRotameterConfigMonitorResolutionPeriod	N/A	
ocHnRotameterConfigQosSegmentId	N/A	
ocHnRotameterConfigEndpointMacAddress	N/A	
Rotameter augmentation table Objects		
ocHnPerStreamRotameterConfigRowStatus	N/A	
ocHnPerStreamRotameterConfigLayer2StreamId	N/A	
ocHnPerStreamRotameterConfigTrafficHandle	N/A	
ocHnPerStreamRotameterConfigObservationActive	N/A	
Dynamic configuration parameters		
ocHnQosStreamsInfoCollectionTrigger	N/A	
QoS traffic descriptor table Objects		
ocHnQosTrafficQDMacAddress	N/A	
ocHnQosTrafficHandle	N/A	
ocHnQosTrafficNetworkAddressType	N/A	
ocHnQosTrafficSourceAddress	N/A	
ocHnQosTrafficSourcePort	N/A	

OCAP HN MIB Object-Type	MoCA11 MIB v1.01 Object-Type	Comments/Notes:
ocHnQosTrafficDestinationAddress	N/A	
ocHnQosTrafficDestinationPort	N/A	
ocHnQosTrafficIpProtocol	N/A	
ocHnQosTrafficV3TrafficIdSourceUuid	N/A	
ocHnQosTrafficV3TrafficIdDestinationUuid	N/A	
ocHnQosTrafficMediaServerConnectionId	N/A	
ocHnQosTrafficMediaRendererConnectionId	N/A	
ocHnQosTrafficLeaseTime	N/A	
ocHnQosTrafficCritical	N/A	
ocHnQosTrafficUserName	N/A	
ocHnQosTrafficVendorApplicationName	N/A	
ocHnQosTrafficPortName	N/A	
ocHnQosTrafficServiceProviderServiceName	N/A	
ocHnQosTrafficCpName	N/A	
TSpec Table		
ocHnQosTspec	N/A	
ocHnQosActiveTspec	N/A	
ocHnQosTspecTrafficClass	N/A	
ocHnQosTspecReqQosType	N/A	
ocHnQosTspecDataRate	N/A	
ocHnQosTspecPeakDataRate	N/A	
ocHnQosTspecMaxBurstSize	N/A	
ocHnQosTspecMaxPacketSize	N/A	
ocHnQosTspecE2EMaxDelayHigh	N/A	
ocHnQosTspecE2EMaxJitter	N/A	
Policy table Objects		
ocHnQosPolicyRuleIdentifier	N/A	
ocHnQosPolicyRowStatus	N/A	
ocHnQosPolicyIpAddressType	N/A	
ocHnQosPolicySourceAddressUpLimit	N/A	
ocHnQosPolicySourceAddressLowLimit	N/A	
ocHnQosPolicySourcePortUpLimit	N/A	
ocHnQosPolicySourcePortLowLimit	N/A	
ocHnQosPolicyDestinationAddressUpLimit	N/A	
ocHnQosPolicyDestinationAddressLowLimit	N/A	
ocHnQosPolicyDestinationPortUpLimit	N/A	
ocHnQosPolicyDestinationPortLowLimit	N/A	
ocHnQosPolicyIpProtocolUpLimit	N/A	

OCAP HN MIB Object-Type	MoCA11 MIB v1.01 Object-Type	Comments/Notes:
ocHnQosPolicyIpProtocolLowLimit	N/A	
ocHnQosPolicyTrafficClass	N/A	
ocHnQosPolicyPeakDataRateUpLimit	N/A	
ocHnQosPolicyPeakDataRateLowLimit	N/A	
ocHnQosPolicyMeanDataRateUpLimit	N/A	
ocHnQosPolicyMeanDataRateLowLimit	N/A	
ocHnQosPolicyMaxBurstSizeUpLimit	N/A	
ocHnQosPolicyMaxBurstSizeLowLimit	N/A	
ocHnQosPolicyE2EMaxDelayHighLimit	N/A	
ocHnQosPolicyE2EMaxDelayLowLimit	N/A	
ocHnQosPolicyBoundaryAddressType	N/A	
ocHnQosPolicyBoundarySourceAddressUpLimit	N/A	
ocHnQosPolicyBoundarySourceAddressLowLimit	N/A	
ocHnQosPolicyBoundaryDestinationAddressUpLimit	N/A	
ocHnQosPolicyBoundaryDestinationAddressLowLimit	N/A	
ocHnQosPolicyUserName	N/A	
ocHnQosPolicyVendorApplicationName	N/A	
ocHnQosPolicyPortName	N/A	
ocHnQosPolicyServiceProviderServiceName	N/A	
ocHnQosPolicyCriticalFlag	N/A	
ocHnQosPolicyRequestedQosType	N/A	
ocHnQosPolicyStartTime	N/A	
ocHnQosPolicyEndTime	N/A	
ocHnQosPolicyTrafficLeaseTimeUpValue	N/A	
ocHnQosPolicyTrafficLeaseTimeLowValue	N/A	
ocHnQosPolicyRuleType	N/A	
ocHnQosPolicyRulePriority	N/A	
ocHnQosPolicyTrafficImportanceNumber	N/A	
ocHnQosPolicyUserImportanceNumber	N/A	
QoS Statistics for RSD Technologies only Objects		
ocHnQosROStatsTable		
ocHnQosROStatsIdentifier	N/A	
ocHnQosROStatsMacAddress	N/A	
ocHnQosROStatsObservationMacAddress	N/A	
ocHnQosROStatsQosSegmentId	N/A	
ocHnQosROStatsTotalTrafficBytes	Not Supported	
ocHnQosROStatsTotalParameterizedBytes	Not Supported	

OCAP HN MIB Object-Type	MoCA11 MIB v1.01 Object-Type	Comments/Notes:
ocHnStreamSummaryTotalParameterizedBytesAllocated	Not Supported	
ocHnQosROStatsTotalParameterizedPackets	Not Supported	The current MoCA MIB does not distinguish total transmitted Parameterized Pkt statistics, it only includes statistics for the interface as a whole, both PQOS and non-PQOS pkts. See mocalfTxPackets.
ocHnQosROStatsTotalParameterizedPacketsDropped	Not supported	The current MoCA MIB does not distinguish total dropped Parameterized Pkt statistics, it only includes statistics for the interface as a whole, both PQOS and non-PQOS pkts. See mocalfRxDrops.
ocHnQosROStatsReportingDateAndTime	N/A	
ocHnQosROStatsObservationPeriod	N/A	
ocHnQosROStatsMonitorResolutionPeriod	N/A	
ocHnQosStreamStatisticsTable		
ocHnQosStreamStatisticsTrafficHandle	N/A	
ocHnQosStreamStatisticsLayer2StreamId	mocalfFlowID	
ocHnQosStreamStatisticsPktsTransmitted	mocalfTxPacketsFlow	
ocHnQosStreamStatisticsPktsReceived	Not supported	The current MoCA MIB does not distinguish received Parameterized Pkt statistics to a specific PQOS flow, it only includes statistics for the interface as a whole, both PQOS and non-PQOS pkts. See mocalfRxPackets.
ocHnQosStreamStatisticsErrorPktsDropped	Not supported	The current MoCA MIB does not distinguish error Parameterized Pkt statistics to a specific PQOS flow, it only includes statistics for the interface as a whole, both PQOS and non-PQOS pkts. See mocalfRxDrops.
ocHnQosStreamStatisticsBytesTransmitted	Not supported	The current MoCA MIB does not distinguish parameterized bit Tx statistics to a specific PQOS flow, it only includes statistics for the interface as a whole, both PQOS and non-PQOS pkts. The MoCA MIB does not address bit level PQOS statistics only Pkts.

OCAP HN MIB Object-Type	MoCA11 MIB v1.01 Object-Type	Comments/Notes:
ocHnQoSStreamStatisticsBytesReceived	Not supported	The current MoCA MIB does not distinguish parameterized bit Rx statistics to a specific PQOS flow, it only includes statistics for the interface as a whole, both PQOS and non-PQOS pkts. The MoCA MIB does not address bit level PQOS statistics only Pkts.
ocHnQoSStreamStatisticsPeakDataRateViolations	Not supported	
QoS Priority-based Statistics for PSD devices only Objects		
ocHnQoSTrafficTotalBytesPriority0	Not supported	
ocHnQoSTrafficTotalBytesPriority1	Not supported	
ocHnQoSTrafficTotalBytesPriority2	Not supported	
ocHnQoSTrafficTotalBytesPriority3	Not supported	
ocHnQoSTrafficTotalBytesPriority4	Not supported	
ocHnQoSTrafficTotalBytesPriority5	Not supported	
ocHnQoSTrafficTotalBytesPriority6	Not supported	
ocHnQoSTrafficTotalBytesPriority7	Not supported	
Device addressing and operational status information Objects		
ocHnDevInterfaceConfigMaxPowerLevel	mocalfTxPowerLimit	Note the Max power "mocalfTxPowerLimit "in the MoCA MIB is an attenuation level value applied to the device's maximum capable MoCA power level.
ocHnDevInterfaceConfigPowerUnits	N/A	
ocHnDevInterfaceConfigMaxParameterizedBandwidth	Not Supported	
ocHnDevInterfaceConfigEnableEncryption	mocalfPrivacyEnable	
ocHnDevInterfaceConfigEncryptionPassphrase	mocalfPassword	
Device Network Operating Status Objects		
ocHnDevInterfaceStatusTxBroadcastRate	mocalfTxGcdRate	
ocHnDevInterfaceStatusTxBroadcastLevel	mocalfTxGcdPowerReduction	The MoCA mocalfTxGcdPowerReduction power reduction attenuation value is combined with the Max power "mocalfTxPowerLimit" in the MoCA MIB which is an attenuation level value applied to the device's maximum capable MoCA power level.

OCAP HN MIB Object-Type	MoCA11 MIB v1.01 Object-Type	Comments/Notes:
ocHnDevInterfaceStatusMaxTxPowerLevel	Not supported	Note the actual MoCA MAX Tx power capability of a device is not identified in the MoCA MIB. The MoCA MIB identifies an attenuation level value applied to the device's maximum capable MoCA power level in the mocaIfTxPowerLimit.
ocHnDevInterfaceStatusPowerUnits	N/A	
ocHnDevInterfaceStatusMaxParameterizedBandwidth	Not Supported	
ocHnDevInterfaceStatusLayer2Scheduler	mocaIfNC	The "mocaIfNC" identifies the MoCA node ID value of the MoCA NC on the network. If the local RSD device's MoCA NodeID is equal to the MoCA node ID contained in the "mocaIfNC" parameter, the local RSD device is the ocHnDevInterfaceStatusLayer2Scheduler .
Logical Device Connection Table Objects		
ocHnDevConnectionDestMac	mocaNodeMacAddress mocaNodeIndex mocaMeshTxNodeIndex mocaMeshRxNodeIndex	
ocHnDevConnectionRxLinkRate	mocaMeshTxRate	The Rx rate is determined in the MoCA MIB by obtaining the Tx rate from a remote node to the local node.
ocHnDevConnectionRxModulationType	Not supported	
ocHnDevConnectionRxBroadcastRate	mocaNodeTxGcdRate	The broadcast Rx rate is determined in the MoCA MIB by obtaining the Broadcast Tx rate from a remote node to the local node.
ocHnDevConnectionRxSignalStrength	mocaNodeRxPower	
ocHnDevConnectionTxUnicastLevel	mocaNodeTxPowerReduction	The MoCA mocaNodeTxPowerReduction power reduction attenuation value is combined with the Max power "mocaIfTxPowerLimit "in the MoCA MIB which is an attenuation level value applied to the device's maximum capable MoCA power level.
ocHnDevConnectionPowerUnits	N/A	
ocHnDevConnectionTxLinkRate	mocaMeshTxRate	
ocHnDevConnectionTxModulationType	Not supported	

Appendix II Revision History

The following ECN was incorporated into OC-SP-MIB-HN-I02-100507:

ECN	Description	Date
MIB-HN-N-10.1540-1	Device Property Additions	4/30/10
